



SMART CAKE 115 IP54 LED GE

Smart cake is part of the Smart family. This family's styling is based on our most popular iconic designs. Its gently sloping sides ensure a soft distribution of light. Since its introduction in 2010, Smart has become an extensive portfolio with a broad range of accessories. Concretely this means that the luminaires consist of a light source (LED, halogen), which can be combined with one of three trims to suit your needs. The new spotlights can be combined with Smart mask, Smart surface box or surface tubed to form the perfect solution for any interior. Choose a white, black or gold finishing. Also available in different sizes, fix and adjustable, IP version, ...

Art. Nr. 12742009

SPECIFICATIONS

| | | | | |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------|---------------|--------|--------|
| Lamp | 1x LED Array | | | |
| Gear / Transfo | LED gear not incl. | | | |
| Cut-out size | ø 108 h 100 | | | |
| Weight | 0.53kg | | | |
| Min. Distance | 0.1 | | | |
| IP | IP54 | | | |
| Glow Wire Test | 960° | | | |
| Source lifetime | 50000 hrs | | | |
| CRI | 90 | | | |
| Power supply | 350mA | 500mA | 700mA | 900mA |
| | 31Vf | 32Vf | 34Vf | 35Vf |
| Connected load | 11W | 16.25W | 23.6W | 31.2W |
| Lumen | 983lm | 1348lm | 1793lm | 2113lm |
| Efficacy | 89lm/W | 43lm/W | 76lm/W | 68lm/W |
| UGR | 19 | 20 | 21 | 22 |
| Adjustability | Not Applicable | | | |
| Remark | ! 3500K on request ! can be combined with Smart mask ! can be combined with Smart surface box & surface tubed (surface/suspension) | | | |

| | WARM WHITE 2700K / CRI 90+ | | | NEUTRAL WHITE 4000K / CRI 90+ | | | WARM WHITE 3000K / CRI 90+ | | |
|-------------|-------------------------------|-------------|--------------|----------------------------------|-------------|--------------|-------------------------------|---------------|--------------|
| | MEDIUM 25° | SPOT 15° | FLOOD 40° | MEDIUM 25° | SPOT 15° | FLOOD 40° | SPOT 15° | MEDIUM 25° | FLOOD 40° |
| black struc | 12742032 | 12742232 | 12742332 | 12742132 | 12742732 | 12742832 | 12742432 | 12742532 | 12742632 |
| gold | 12742046 | 12742246 | 12742346 | 12742146 | 12742746 | 12742846 | 12742446 | 12742546 | 12742646 |
| white struc | 12742009 | 12742209 | 12742309 | 12742109 | 12742709 | 12742809 | 12742409 | 12742509 | 12742609 |



This label is available in other languages:
<http://supermodular.com/assets/TYPE2.pdf>



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

SMART CAKE 115 IP54 LED GE

ACCESSORIES

GYPKIT

12290530 | GYPKIT 190X190 - Ø108

CONBOX

10889830 | CONBOX 190X192X130X256

MASK

12810032 | SMART MASK 115 1X BLACK STRUC
 12810046 | SMART MASK 115 1X GOLD
 12810009 | SMART MASK 115 1X WHITE STRUC
 12810132 | SMART MASK 115 2X BLACK STRUC
 12810146 | SMART MASK 115 2X GOLD
 12810109 | SMART MASK 115 2X WHITE STRUC

RECESSED-FRAME

12810230 | RECESSED RING Ø127 H100

SURFACE-TUBED

13140332 | SMART SURFACE TUBED 115 LED DALI GI BLACK STRUC
 13140324 | SMART SURFACE TUBED 115 LED DALI GI BRUSHED ALU
 13140309 | SMART SURFACE TUBED 115 LED DALI GI WHITE STRUC
 13140232 | SMART SURFACE TUBED 115 LED 1-10V/PUSHDIM GI BLACK STRUC
 13140224 | SMART SURFACE TUBED 115 LED 1-10V/PUSHDIM GI BRUSHED ALU
 13140209 | SMART SURFACE TUBED 115 LED 1-10V/PUSHDIM GI WHITE STRUC
 13140132 | SMART SURFACE TUBED 115 LED TRE DIM GI BLACK STRUC
 13140124 | SMART SURFACE TUBED 115 LED TRE DIM GI BRUSHED ALU
 13140109 | SMART SURFACE TUBED 115 LED TRE DIM GI WHITE STRUC
 13141332 | SMART SURFACE TUBED SUSPENSION 115 LED DALI GI BLACK STRUC
 13141324 | SMART SURFACE TUBED SUSPENSION 115 LED DALI GI BRUSHED ALU
 13141309 | SMART SURFACE TUBED SUSPENSION 115 LED DALI GI WHITE STRUC
 13141232 | SMART SURFACE TUBED SUSPENSION 115 LED 1-10V/PUSHDIM GI BLACK STRUC
 13141224 | SMART SURFACE TUBED SUSPENSION 115 LED 1-10V/PUSHDIM GI BRUSHED ALU
 13141209 | SMART SURFACE TUBED SUSPENSION 115 LED 1-10V/PUSHDIM GI WHITE STRUC
 13141132 | SMART SURFACE TUBED SUSPENSION 115 LED TRE DIM GI BLACK STRUC
 13141124 | SMART SURFACE TUBED SUSPENSION 115 LED TRE DIM GI BRUSHED ALU
 13141109 | SMART SURFACE TUBED SUSPENSION 115 LED TRE DIM GI WHITE STRUC



