

Blacklight BL368 Linear & Circline

FC32 T12 BL 368 8

0000100



Range Features

- Features
- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12, T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

EAN-code	5410288001005
Kap/Voet	G10q
Watt (nominaal) (W)	32
Bestelnummer	0000100
Spanning (V)	57

DATA TABLE

General data

EAN-code	5410288001005
Kap/Voet	G10q
Bestelnummer	0000100

Blacklight BL368 Linear & Circline

FC32 T12 BL 368 8

0000100

Lange beschrijving

Features

BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency

100% improvement in effectiveness (at 368nm)

Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)

Performs longer and better throughout the insect season

Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes

Applications

Insect traps, insect attraction is strongly increased

Restaurants, kitchens, food shops, supermarkets

Diazo printing machines

Photo Polymerisation

Chemical processing

Mineral detection

Various technical applications

Directions for use

Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage

Productnaam	FC32 T12 BL 368 8
Hoeveelheid verpakking verkoop	12
E-nummer FI	4940429

Electrical data

Watt (nominaal) (W)	32
Spanning (V)	57

Physical data

Beschrijving verpakking	Box/Sleeve
Gewicht (kg)	0.12

TECHNICAL DRAWINGS

Blacklight BL368 Linear & Circline

FC32 T12 BL 368 8

0000100

