




# SNEAK TRIMLESS

CEILING RECESSED




## 1.0 LED

LED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.19 kg IP20 0.3-1° 32°

86x86 35°/35° 355° 95



## 2.0 LED

2xLED 7/10W | 350-500mA | 18Vf  
COB 3-step | excl. power supply  
aluminium powder coated

0.34 kg IP20 0.3-1° 32°

86x156 35°/35° 355° 95

CODE	
155151W	155151B

### Light Colour Selection

LUMEN	CRI	CODE
2700K	335-470   >90	3
3000K	375-510   >90	5
1800-2850K	255-350   >95	9

CODE	
155251W	155251B

### Light Colour Selection

LUMEN	CRI	CODE
2700K	2x335-470   >90	3
3000K	2x375-510   >90	5
1800-2850K	2x255-350   >95	9

## ALWAYS USE

plastic plasterkit 10 or 13

CODE	
90017122	90017116

aluminium plasterkit 4-25

90017120
----------

power supply

CODE	
350mA   10W	90223401
500mA   10W	90214404
500mA   15W dim	90224501

more power supplies on page 574

## ALWAYS USE

plastic plasterkit 10 or 13

CODE	
90017123	90017117

aluminium plasterkit 4-25

90017121
----------

power supply

CODE	
350mA   10W	90223401
500mA   10W	90214404
500mA   15W dim	90224501

more power supplies on page 574