

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Accessories for D-SERIES relays include:

- Relay bases
- LED / Protective modules
- Metal retaining clips

General ordering data

Type	SCM 4CO ECO
Order No.	7760056264
Version	D-SERIES DRM, Relay base, Continuous current: 4 x 6 A, Screw connection
GTIN (EAN)	6944169662973
Qty.	10 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	27 mm	Height	75 mm
Depth	61 mm	Net weight	68 g

Temperatures

Humidity	35...85 % rel. humidity, no condensation	Operating temperature	-40 °C...70 °C
Storage temperature	-40 °C...70 °C		

Output

Max. switching voltage, AC	300 V	Continuous current	4 x 6 A
----------------------------	-------	--------------------	---------

Insulation coordination

Dielectric strength input – output	4 kV _{eff}	Protection degree	IP 20
------------------------------------	---------------------	-------------------	-------

Further details of approvals / standards

Certificate No. (cURus)	E312083
-------------------------	---------

Connection data

Wire connection method	Screw connection	Tightening torque, min.	0.5 Nm
Tightening torque, max.	0.8 Nm	Clamping range, rated connection, min.	0.5 mm ²
Clamping range, rated connection, max.	2.5 mm ²	Stripping length, rated connection	8 mm
Wire cross-section, solid, min.	0.5 mm ²	Wire cross-section, solid, max.	2.5 mm ²
Wire connection cross-section, finely stranded, min.	0.5 mm ²	Wire connection cross section, finely stranded, max.	2.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), max.	1.5 mm ²
Cross-section for connected conductor, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, min.	0.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules and plastic collars DIN 46228/4, rated connection, max.	1.5 mm ²
Wire connection cross section, finely stranded, two clampable wires, min.	0.5 mm ²	Wire cross-section, finely stranded, two clampable wires, max.	1.5 mm ²

Classifications

ETIM 3.0	EC001456	ETIM 5.0	EC001456
ETIM 6.0	EC001456	eClass 6.2	27-37-16-03
eClass 7.1	27-37-16-03	eClass 8.1	27-37-16-03
eClass 9.0	27-37-16-03		

Approvals

Approvals


Downloads

 Declaration of Conformity [K550_10_13.pdf](#)


Creation date March 11, 2015 2:30:41 PM CET

Data sheet

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)
with LED


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270024L Au	7760056183	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 5µm Au, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection	4032248922222	20 pc(s).
DRM270730L Au	7760056184	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 5µm Au, Rated control voltage: 230 V AC, Continuous current: 10 A, Plug-in connection	4032248922239	20 pc(s).

with LED and free-wheel diode


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270024LD Au	760056124	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection	4032248855544	20 pc(s).
DRM270024LD Au	760056077	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V	4032248855780	20 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)

DC, Continuous current: 10
 A, Plug-in connection

standard relay


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM570548	7760056084	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 5 A, Plug-in connection	4032248855 193 20	pc(s).
DRM570048	7760056080	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 5 A, Plug-in connection	4032248855 148 20	pc(s).
DRM570220	7760056082	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 5 A, Plug-in connection	4032248855 162 20	pc(s).
DRM570615	7760056085	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 115 V AC, Continuous current: 5 A, Plug-in connection	4032248855 230 20	pc(s).
DRM570524	7760056083	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 5 A, Plug-in connection	4032248855 186 20	pc(s).
DRM570110	7760056081	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 5 A, Plug-in connection	4032248855 131 20	pc(s).

D-SERIES DRM SCM 4CO ECO

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)

DRM570012 7760056078	D-SERIES DRM, Relais, No. 4032248855117 20 pc(s). of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 12 V DC, Continuous current: 5 A, Plug-in connection
DRM570024 7760056079	D-SERIES DRM, Relais, No. 4032248855124 20 pc(s). of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection
DRM570730 7760056086	D-SERIES DRM, Relais, No. 4032248855254 20 pc(s). of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in connection

with LED and test button



Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM570110L	7760056099	D-SERIES DRM, Relais, No. 4032248855650 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 5 A, Plug-in connection	4032248855650	20 pc(s).
DRM570615L	7760056103	D-SERIES DRM, Relais, No. 4032248855612 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 115 V AC, Continuous current: 5 A, Plug-in connection	4032248855612	20 pc(s).
DRM570524L	7760056101	D-SERIES DRM, Relais, No. 4032248855636 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 5 A, Plug-in connection	4032248855636	20 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Mating connector (fully pluggable)

DRM570012L 7760056096	D-SERIES DRM, Relais, No. 4032248855681 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 12 V DC, Continuous current: 5 A, Plug-in connection
DRM570730L 7760056104	D-SERIES DRM, Relais, No. 4032248855605 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in connection
DRM570220L 7760056100	D-SERIES DRM, Relais, No. 4032248855643 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 5 A, Plug-in connection
DRM570548L 7760056102	D-SERIES DRM, Relais, No. 4032248855629 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 5 A, Plug-in connection
DRM570048L 7760056098	D-SERIES DRM, Relais, No. 4032248855667 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 5 A, Plug-in connection
DRM570024L 7760056097	D-SERIES DRM, Relais, No. 4032248855674 20 pc(s). of contacts: 4, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)
with LED


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270024L	7760056060	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection	4032248855957	20 pc(s).
DRM270012L	7760056059	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 12 V DC, Continuous current: 10 A, Plug-in connection	4032248855964	20 pc(s).
DRM270125L	7760056115	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 125 V DC, Continuous current: 10 A, Plug-in connection	4032248883110	20 pc(s).
DRM270048L	7760056061	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 10 A, Plug-in connection	4032248855940	20 pc(s).
DRM270548L	7760056065	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 10 A, Plug-in connection	4032248855902	20 pc(s).
DRM270524L	7760056064	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 10 A, Plug-in connection	4032248855919	20 pc(s).
DRM270615L	7760056066	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 115	4032248855896	20 pc(s).

Creation date March 11, 2015 2:30:42 PM CET

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Mating connector (fully pluggable)

	V AC, Continuous current: 10 A, Plug-in connection
DRM270730L 7760056067	D-SERIES DRM, Relais, No. 4032248855889 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 10 A, Plug-in connection
DRM270220L 7760056063	D-SERIES DRM, Relais, No. 4032248855926 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 10 A, Plug-in connection
DRM270110L 7760056062	D-SERIES DRM, Relais, No. 4032248855933 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 10 A, Plug-in connection

with LED and free-wheel diode


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green)
and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
		D-SERIES DRM, Relais, No.	4032248855599	20 pc(s).
	DRM570024L D760056105	of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection		
		D-SERIES DRM, Relais, No.	4032248855551	20 pc(s).
	DRM570024L D760056123	of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection		

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)
with LED and test button


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270024L	760056185	D-SERIES DRM, Relais, No. of contacts: 2, CO contact with test button, AgNi 5µm Au, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection	4032248922246	20 pc(s).
DRM270730L	760056186	D-SERIES DRM, Relais, No. of contacts: 2, CO contact with test button, AgNi 5µm Au, Rated control voltage: 230 V AC, Continuous current: 10 A, Plug-in connection	4032248922253	20 pc(s).

with LED and test button


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270048L	760056070	D-SERIES DRM, Relais, No. of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 10 A, Plug-in connection	4032248855858	20 pc(s).
DRM270615L	760056070	D-SERIES DRM, Relais, No. of contacts: 2, CO contact with test button, AgNi	4032248855803	20 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Mating connector (fully pluggable)

	0.15 gold flashed, Rated control voltage: 115 V AC, Continuous current: 10 A, Plug-in connection
DRM270524LT760056073	D-SERIES DRM, Relais, No. 4032248855827 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 10 A, Plug-in connection
DRM270730LT760056076	D-SERIES DRM, Relais, No. 4032248855797 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 10 A, Plug-in connection
DRM270012LT760056068	D-SERIES DRM, Relais, No. 4032248855872 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 12 V DC, Continuous current: 10 A, Plug-in connection
DRM270024LT760056069	D-SERIES DRM, Relais, No. 4032248855865 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection
DRM270548LT760056074	D-SERIES DRM, Relais, No. 4032248855810 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 10 A, Plug-in connection
DRM270110LT760056071	D-SERIES DRM, Relais, No. 4032248855841 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 10 A, Plug-in connection
DRM270220LT760056072	D-SERIES DRM, Relais, No. 4032248855834 20 pc(s). of contacts: 2, CO contact with test button, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 10 A, Plug-in connection

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)
with LED


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM570615L	7760056094	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 115 V AC, Continuous current: 5 A, Plug-in connection	4032248855704	20 pc(s).
DRM570730L	7760056095	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in connection	4032248855698	20 pc(s).
DRM570548L	7760056093	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 5 A, Plug-in connection	4032248855711	20 pc(s).
DRM570524L	7760056092	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 5 A, Plug-in connection	4032248855728	20 pc(s).
DRM570048L	7760056089	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 5 A, Plug-in connection	4032248855759	20 pc(s).
DRM570024L	7760056088	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection	4032248855766	20 pc(s).
DRM570012L	7760056087	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 12 V	4032248855773	20 pc(s).

D-SERIES DRM SCM 4CO ECO

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)

	DC, Continuous current: 5 A, Plug-in connection
DRM570110L 7760056090	D-SERIES DRM, Relais, No. 4032248855742 20 pc(s). of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 5 A, Plug-in connection
DRM570220L 7760056091	D-SERIES DRM, Relais, No. 4032248855735 20 pc(s). of contacts: 4, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 5 A, Plug-in connection

with LED and test button



Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM570220L 7760056287 AU		D-SERIES DRM, Relais, No. of contacts: 4, CO contact with test button, AgNi 5µm Au, Rated control voltage: 220 V DC, Continuous current: 5 A, Plug-in connection	6944 169722516 20 pc(s).	
DRM570730L 7760056190 Au		D-SERIES DRM, Relais, No. of contacts: 4, CO contact with test button, AgNi 5µm Au, Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in connection	4032248922291 20 pc(s).	
DRM570024L 7760056189 Au		D-SERIES DRM, Relais, No. of contacts: 4, CO contact with test button, AgNi 5µm Au, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection	4032248922284 20 pc(s).	

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)
with LED


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM570730L Au	7760056188	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 5µm Au, Rated control voltage: 230 V AC, Continuous current: 5 A, Plug-in connection	4032248922277	20 pc(s).
DRM570024L Au	7760056187	D-SERIES DRM, Relais, No. of contacts: 4, CO contact, AgNi 5µm Au, Rated control voltage: 24 V DC, Continuous current: 5 A, Plug-in connection	4032248922260	20 pc(s).

standard relay


Relay from the D-SERIES DRM.

- 2 or 4 CO contacts
- Compact design
- Wide range of coil voltages
- Optional test button (AC red, DC blue)
- Optional with integrated status display (AC red, DC green) and/or free-wheel diode

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM270110	7760056053	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 110 V DC, Continuous current: 10 A, Plug-in connection	4032248856022	20 pc(s).
DRM270615	7760056057	D-SERIES DRM, Relais, No. of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 115 V AC, Continuous current: 10 A, Plug-in connection	403224885988	20 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Mating connector (fully pluggable)

DRM270524 7760056055	D-SERIES DRM, Relais, No. 4032248856008 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V AC, Continuous current: 10 A, Plug-in connection
DRM270220 7760056054	D-SERIES DRM, Relais, No. 4032248856015 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 220 V DC, Continuous current: 10 A, Plug-in connection
DRM270730 7760056058	D-SERIES DRM, Relais, No. 4032248855971 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 230 V AC, Continuous current: 10 A, Plug-in connection
DRM270048 7760056052	D-SERIES DRM, Relais, No. 4032248856039 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V DC, Continuous current: 10 A, Plug-in connection
DRM270024 7760056051	D-SERIES DRM, Relais, No. 4032248856046 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 24 V DC, Continuous current: 10 A, Plug-in connection
DRM270548 7760056056	D-SERIES DRM, Relais, No. 4032248855995 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 48 V AC, Continuous current: 10 A, Plug-in connection
DRM270012 7760056050	D-SERIES DRM, Relais, No. 4032248856053 20 pc(s). of contacts: 2, CO contact, AgNi 0.15 gold flashed, Rated control voltage: 12 V DC, Continuous current: 10 A, Plug-in connection

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

LED



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 3 110/230VUC	7940018455	D-SERIES, LED module, Rated control voltage: 110... 230 V UC	4032248878185	20 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Protective modules



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 3 110/230VAC	7760056014	D-SERIES, RC filter, Rated control voltage: 110...230 V AC	4032248878109	10 pc(s).
2012-11-01TORRIDIO/230VAC	7760056169	D-SERIES, Free-wheel diode, Rated control voltage: 6...230 V	4032248967728	10 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

LED



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 3 6/24VUC	7940018457	D-SERIES, LED module, Rated control voltage: 6...24 V UC	4032248878192	20 pc(s).
RIM 3 24/60VUC	7760056018	D-SERIES, LED module, Rated control voltage: 24... 60 V UC	4032248878130	10 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Retaining clip



Accessories for D-SERIES relays include:

- Relay bases
- LED / Protective modules
- Metal retaining clips

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
DRM/DRL CLIP M	7760056108	D-SERIES, Retaining clip	403224885568	10 pc(s).

Protective modules



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 3 110/230Vac LED	7760056045	D-SERIES, RC filter, Rated control voltage: 110...230 V AC	4032248878147	10 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

LED / free-wheel diode



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 2 6/24VDC	7760056015	D-SERIES, LED module with freewheel diode, Rated control voltage: 6...24 V DC	4032248878116	10 pc(s).
RIM 2 110/230VDC	7760056017	D-SERIES, LED module with freewheel diode, Rated control voltage: 110...230 V DC	4032248896615	10 pc(s).

**D-SERIES DRM
SCM 4CO ECO**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

LED / free-wheel diode



You place stringent demands on your relay combinations in industrial environments. Our D-SERIES relay modules were designed specifically for challenging industrial applications. Let's connect. In many industrial applications voltages between 110 and 220 V are used to control actuators. With load currents exceeding 100 mA these high voltages produce arcing that causes a great deal of wear on the relay contacts. We have designed our D-SERIES relay modules specifically for universal usage in a wide range of industrial applications. They are much more reliable than conventional solutions, which minimises costs for maintenance and replacement. Thanks to series connected contacts, built-in blow magnets and low-wear contacts, arcing is effectively suppressed with D-SERIES products – resulting in a noticeably longer service life.

General ordering data

Type	Order No.	Version	GTIN (EAN)	Qty.
RIM 2 24/60VDC	7760056016	D-SERIES, LED module with freewheel diode, Rated control voltage: 24...60 V DC	4032248878123	10 pc(s).

Addresses worldwide

Let's connect.

- AE United Arab Emirates**
Weidmüller Middle East FZE
Warehouse Q3-79
SAIF-Zone
P.O. BOX 8591
Sharjah
Telephone number +971 65572723
Fax number +971 65572724
wme.info@weidmueller.com
- AO Angola**
Please contact
Phambili Interface
South Africa
- AR Argentina**
CPI SA
Bauness 2660
C1431DOF Buenos Aires
Telephone number +54 11 4523 8008
Fax number +54 11 4522 0546
info@cpi.com.ar
www.cpi.com.ar
- AT Austria**
Weidmüller GmbH
IZ NOE Süd Straße 2b, Obj
M 59
2355 Wiener Neudorf
Telephone number +43 2236 67080
Fax number +43 2236 6708-899
office.at@weidmueller.com
www.weidmueller.com
- AU Australia**
Weidmüller Pty. Ltd.
PO BOX 6944
Huntingwood 2148
Huntingwood Drive 43
Huntingwood NSW 2148
Telephone number +61 2 9671 9999
Fax number +61 2 9671 9911
info@weidmuller.com.au
www.weidmuller.com.au
- AZ Azerbaijan**
Representative Office
Rashad Mahmudov
Demirchi Tower, 4th floor
37, Khojali ave.
AZ 1025 Baku
Telephone number +994 12 488 80 36
Fax number +994 12 488 80 37
rashad.mahmudov@weidmueller.com
- BA Bosnia and Herzegovina**
Please contact
our Representative Office
Weidmüller Interface GmbH
& Co. KG
Serbia

or

BIG electric d.o.o
Mladena Stojanovića 117A
78000 Banja Luka
Telephone number +387 51926277
Fax number +387 51926277
bigelectric@blic.net
www.bigelectric.ba
- BE Belgium**
Weidmüller Benelux B. V.
Mechelsesteenweg 519 bus
6 an 7
1930 Nossegem
Telephone number +32 2 752 40 70
Fax number +32 2 751 36 06
info@weidmueller.be
www.weidmueller.be
- BG Bulgaria**
Weid-Bul EOOD
Bul. "Kliment Ohridski" 13
1756 Sofia
Telephone number +359 2 963 2560
Fax number +359 2 963 1098
sofia@weidbul.com
www.weidbul.com
- BH Bahrain**
Khayber Trading Company
P.O Box 1976
Manama
Telephone number +973 720747
Fax number +973 720331
khayber@batelco.com.bh
- BR Brazil**
Weidmüller Conexel do Brasil
Conexões Elétricas Ltda.
Av. Presidente Juscelino, 642
- Piraporinha
Diadema, São Paulo
09950-370
Telephone number +55 (11) 4366-9600
Fax number +55 (11) 4362-1677
vendas@weidmueller.com.br
www.weidmueller.com.br
- BW Botswana**
Please contact
Phambili Interface
South Africa
- BY Belarus**
TECHNIKON Ltd.
Nezavisimosti pr. 177-9
220125 Minsk
Telephone number +375 17 393-11-77
Fax number +375 17 3930080
wm@technikon.by
- CA Canada**
W Interconnections Canada
Inc.
10 Spy Court
Markham Ontario L3R 5H6
Telephone number +1 (905) 475-1507 Ext. 9836
Fax number +1 (905) 475-2798
support@weidmuller.ca
www.weidmuller.ca
- CG Congo**
Please contact
Phambili Interface
South Africa
- CH Switzerland**
Weidmüller Schweiz AG
Rundbuckstraße 2
8212 Neuhausen am
Rheinfall SH
Telephone number +41 52 674 07 07
Fax number +41 52 674 07 08
info@weidmueller.ch
www.weidmueller.ch
- CL Chile**
ATS - INTECH
María Luisa Santander 0475
Santiago
Providencia 7500859
Telephone number +56 2 341 1271
Fax number +56 2 341 1275
felipe@atsintech.com
www.atsintech.com

CPI CHILE LTDA
Av. Presidente Frei Montalva
6001, 47 complejo el cortijo
Santiago - Conchalí
Telephone number +562 963 8440
Fax number +562 963 8440
cpi@cpichile.cl
www.cpi Chile.cl
- CN China**
Weidmüller Interface
(Shanghai) Co. Ltd.
100 Yutong Road
25 F, BM Intercontinental
Business Center
200070 Shanghai
Telephone number +86 21-22195008
Fax number +86 512-68417505
customer.hotline@weidmueller.com.cn
www.cnweidmuller.com
- CO Colombia**
Automatización Avanzada
S. A.
Carrera 97 No., 24 c - 23
Bodega 4
110911 Bogotá-D.C.
Telephone number +57 (1) 547-8510
Fax number +57 (1) 422-3044
comercial@automatizacionavanzada.com
www.automatizacionavanzada.com
- CR Costa Rica**
ELVATRON S. A.
la Uruca 400 Norte Banco
Costa Rica
San Jose Costa Rica
Telephone number +506 2961-060
Fax number +506 5200-609
dirk.haase@elvatron.com
www.elvatron.com
- CZ Czech Republic**
Weidmüller s.r.o.
Lomnického 5/1705
140 00 Praha 4
Telephone number +420 244 001 400
Fax number +420 244 001 499
office@weidmueller.cz
www.weidmueller.cz
- DE Germany**
Weidmüller GmbH & Co. KG
Ohmstraße 9
32758 Detmold
Postfach 30 54
32720 Detmold
Telephone number +49 5231 1428-0
Fax number +49 5231 14-292083
weidmuller@weidmueller.de
www.weidmueller.de
- DK Denmark**
Weidmüller Danmark
Vallensbækvej 18A
2605 Brøndby
Telephone number +45 27747800
kundeservice@weidmuller.dk
www.weidmuller.dk
- DZ Algeria**
SARL INTER ELECTRIC
1a Angles des Rues Okba Ibn
Nafaa et Hassi Beida
2300 Annaba
Telephone number
Fax number
contact@inter-electric.com
- EC Ecuador**
Elsystec S. A., Electricidad
Sistemas y Tecnología
Vasco de Contreras N35-251
y Manosca
Quito - Pichincha
Telephone number +593 22456510
Fax number +593 22456755
Elsystec@uio.satnet.net
- EE Estonia**
Please contact
our Representative Office
Weidmüller Interface GmbH
& Co. KG
Latvia


or


Soots Interface OÜ
Pänu mnt 142
11317 Tallinn
Telephone number +372 609 6933
Fax number
info@sootsinterface.ee
www.sootsinterface.ee
- EG Egypt**
Standard Electric (OMEGA)
1, Abdelhamid Badawy Street
Heliopolis
Cairo
Telephone number +202 21805111
Fax number +202 21805600
stdelec@rite.com
- ES Spain**
Weidmüller, S. A.
Narcís Monturiol 11-13, Pol.
Ind. Sudoeste
8960 Sant Just
Desvern - Barcelona
Telephone number +34 934 803 386
Fax number +34 933 718 055
weidmuller@weidmuller.es
www.weidmuller.es
- FI Finland**
Weidmüller Suomi,
Weidmüller Aktiebolagetin
sivuliike
Koy Plaza Vivace
Äyritie 8C
FI 15100 Vantaa
Telephone number +358 20 7351300
Fax number +358 800 114 667
asiakaspalvelu@weidmuller.fi
www.weidmuller.fi
- FR France**
Weidmüller E. U. R. L.
12, Chaussée Jules César
BP 263 Osny
95523 Cergy-Pontoise Cedex
Telephone number +33 1 34 24 55 00
Fax number +33 1 34 24 55 01
mail@weidmuller.fr
- GB Great Britain**
Weidmüller Ltd.
Klippon House
Centurion Court Office Park,
Meridian East, Meridian
Business Park
Leicester
LE19 1TP
Telephone number +44 116 282 3470
Fax number +44 116 289 3582
marketing@weidmuller.co.uk
www.weidmuller.co.uk
- GE Georgia**
Please contact
our Representative Office
Rashad Mahmudov
Azerbaijan.
- GH Ghana**
Please contact
Weidmüller Interface GmbH
& Co. KG
South Africa
- GR Greece**
G.A. Solutions
Ippokratous 11 Metamorfoisi
144 52 Athen
Telephone number +30 210 2823233
Fax number +30 210 2823233
info@weidmuller.gr
www.weidmuller.gr
- GT Guatemala**
Prestelectro, Prestegard
Electro, S.A.
Avenida Petapa 44-22,
Zona 12
Guatemala City
Telephone number +502 2442-3346
Fax number +502 2476-8945
ventas@preselectro.com
- HK Hong Kong**
Weidmüller (Hong Kong)
Limited Co. Ltd.
Unit 1617, Metropolis Tower
No. 10 Metropolis Drive,
Hung Hom, Kowloon
Telephone number +852 3154 8088
Fax number +852 31548099
Info-hk@weidmueller.com.hk
- HR Croatia**
ElektroPARTNER d.o.o.
Slavonska avenija 24/6
HR-10000 Zagreb
Telephone number +385 (1) 6184 793
Fax number +385 (1) 6184 795
elektropartner@zg.t-com.hr
www.elektropartner.hr
- HU Hungary**
Weidmüller Kereskedelmi Kft.
Budapest
Gubacsi út 6.
1097
Telephone number +36 1 382 7700
Fax number +36 1 382 7701
info@weidmueller.hu
www.weidmueller.hu
- ID Indonesia**
PT. Nego Electrindo
Ruko Mega Grosir Cempaka
Mas Blok I No. 20 – 22
Jakarta 10640
Telephone number +62 21 42882255
Fax number +62 21 42882266
sales@negoelectrindo.co.id
- IE Ireland**
Please contact
Weidmüller Ltd.
Great Britain
- IL Israel**
A. U. Shay Ltd.
23/25, Embarr Street
49222 Petach-Tikva
P.O. Box 1 00 49
49222 Petach-Tikva
Telephone number +972 3-923-3601
Fax number +972 3-923-4601
shay@uriel-shay.com
www.uriel-shay.com


ATEKA Ltd.
4, Ha Tavor lane Industrial
area Segula
49691 Petach-Tikva
P.O. Box 4710
Petach-Tikva
Telephone number +972 73-200-1311
Fax number +972 3-924 4245
marketing@ateka.co.il
www.ateka.co.il
- IN India**
Representative Office
Weidmüller Electronics India
Pvt. Ltd.
12th Lane North Avenue, Opp
Joggers Park,
Kalyani Nagar, Pune
411 006
Telephone number +91 20-41290090
wmi.pune@weidmueller.in
www.weidmueller.com
- IS Iceland**
Samey Automation Center
Lýngas 13
210 Garoabaer
Telephone number +354 510 5200
Fax number +354 5 10 5201
Samey@samey.is
www.samey.is
- IT Italy**
Weidmüller S. r.l.
Via Albert Einstein 4
20092 Cinisello
Balsamo Milano
Telephone number +39 02 660681
Fax number +39 02 6124945
weidmuller@weidmuller.it
www.weidmuller.it
- JM Jamaica**
Please contact
W Interconnections Inc.
United States
- JO Jordan**
Trans Jordan for Electro
PO Box 33 06 07
Amman
Telephone number +962 6 533 2020
Fax number +962 6 533 5800
transjordan@batelco.jo



You can find all Weidmüller addresses and your local contact on the internet at: www.weidmueller.com/countries

Sales company 

Representation abroad 

without representation abroad 

Let's connect.

- JP Japan**
Nihon Weidmüller Co. Ltd.
Sphere Tower Tennoz 2-2-8
Higashi-Shinagawa,
Shinagawa-ku
Tokyo
140-0002
Telephone number +81 3
6711 5300
Fax number +81 3 6711
5333
weidmullerjapan@weidmuller.
co.jp
www.weidmuller.co.jp
- KE Kenya**
Please contact
Phambili Interface
South Africa
- KR Korea**
Weidmuller Korea Co. Ltd.
9th floor, Wonbang B/D
Samseong 2-Dong, Gangnam-
Gu
Seoul 143-42
Telephone number +82
2-516-0003
Fax number +82 2-516-0090
info@weidmuller.co.kr
www.weidmuller.co.kr
- KW Kuwait**
Kana Controls General Trading
& Contracting Co. W. L. L.
Al Rai Industrial Area, Plot
28-30, St. 31
13016 Safat
B.P. 25593
Telephone number +965
4741373
Fax number +965 4741537
info@kanacontrols.com
- KZ Kazakhstan**
Please contact
OOO Weidmüller
Russia
- LB Lebanon**
Progress Engineering &
Trading Enterprises
Al Nahr Street
Beirut 11-1111
Telephone number +961 1
444 664
Fax number +961 1 561 880
progress@inco.com.lb
- LT Lithuania**
Please contact
our Representative Office
Weidmüller Interface GmbH
& Co. KG
Latvia
or
ELEKTROS IRANGA
Tinklu g. 29 a
LT-5319 Panevezys
Telephone number +370 (45)
582 828
Fax number
info@eliranga.lt
- LU Luxembourg**
Please contact
Weidmüller Benelux B. V.
Netherlands
- LV Latvia**
SIA Abi4
Daugavgrivas 31b
Riga, LV-1007
Telephone number +371 674
70999
Fax number +371 676
24562
abi_4@tvnet.lv
Representative Office
Weidmüller Interface GmbH
& Co. KG
Udens str. 12-118
Riga, LV-1007
Telephone number +371
29254766
Fax number +371 674
65637
lgonis.rudaks@weidmueller.
com
www.weidmueller.com
- MA Morocco**
Sofimed
137, Bd Moulay Ismail Roches
Noires
20290 Casablanca
Telephone number
Fax number
contact@sofimedmaroc.com
- MD Moldova**
BERHORD A & D srl
79/1. str. Milescu Spartaru
MD-2075 Chisinau
Moldova
Telephone number +373 (22)
815002
Fax number +373 (22)
815007
atuleanu@berhord.com
www.ad.berhord.com
- ME Montenegro**
Please contact
our Representative Office
Weidmüller Interface GmbH
& Co. KG
Serbia.
- MG Madagascar**
Please contact
Phambili Interface
South Africa
- MK Macedonia**
Please contact
our Representative Office
Weidmüller Interface GmbH
& Co. KG
Serbia
or
ELEKTRO - SMK doool
UL. III Makedonska brigada
b.b.
1000 Skopje
Telephone number +389
22460295
Fax number
Elektro-smk@tekelelab.net.mk
- MT Malta**
E. S. S., Electrical Supplies &
Services Ltd.
San Gwakkin Road
Mriehel
Telephone number +356
21255777
Fax number +356 21255999
robert.agius@ess.com.mt
- MU Mauritius**
Mubelo Electrical Ltd.
Office 26, Gateway building,
St Jean Road
Quatre Bornes
Mauritius
Telephone number +230
4670989
Fax number +230 4654051
richard.mubelo@orange.mu
- MW Malawi**
Please contact
Phambili Interface
South Africa
- MX Mexico**
W Interconnections S. A.
DE C. V.
Blvd. Hermanos Serdán 698,
Col. San Rafael Oriente
72029 Puebla
Telephone number +52 (222)
268 6227
Fax number +52 (222) 286
6242
clientes@weidmuller.com.mx
- MY Malaysia**
Connect Plus Technology
Sdn Bhd
No. 43, Jalan PJS 11/22,
Bandar Sunway
46150 Petaling Jaya
Selangor Darul Ehsan
Telephone number +60 3
5633 7363
Fax number +60 3 5633
6562
paul@cptech.com.my
www.cptech.com.my
- MZ Mozambique**
Please contact
Phambili Interface
South Africa
- NA Namibia**
Please contact
Phambili Interface
South Africa
- NG Nigeria**
Please contact
Weidmüller Interface GmbH
& Co. KG
South Africa
- NL Netherlands**
Weidmüller Benelux B. V.
Franciscusweg 221
1216 SE Hilversum
P.O. Box 1505
1200 BM Hilversum
Telephone number +31 35
626 12 61
Fax number +31 35 623
20 44
info@weidmuller.nl
www.weidmuller.nl
- NO Norway**
Sivilingeniør J.F. Knudtzen AS
Billingstadsletta 97
1396 Billingstad
PO Box 160
1378 Nesbru
Telephone number +47 66
98 33 50
Fax number +47 66 98 09 55
firmapost@fknudtzen.no
www.fknudtzen.no
- NZ New Zealand**
Cuthbert S. Steward Ltd.
27 Te Puni Street
Petone
PO Box 38496
Wellington Mail Centre 5054
Telephone number (04) 568
6156
Fax number (09) 489 1752
csl@cuthbertstewart.co.nz
Cuthbert S. Steward Ltd
4 Fred Thomas Drive
Aon Building, Ground Floor,
South Entry
Takapuna
PO Box 100 338
North Shore City 745
Telephone number (09) 489
1751
Fax number (04) 568 6056
cslak@cuthbertstewart.co.nz
- OM Oman**
DAN INTERNATIONAL LLC.
Ghala St. 111
BP 2901
Seeb
Telephone number +968
5036 77
Fax number +968 5037 55
yedu@danintl.com
- PE Peru**
IMPEXINCA S.A.C.
Calle Ortiz de Zevallos No.
105, Urb. San Antonio
18
Lima, Miraflores
Telephone number +51 1
447 5608
info@impexinca.pe
www.impexinca.pe
J & W CIA. S. A.
Calle 6 Mz. D Lte. 23, Urb.
Ind. Grimanesa
01
Callao
Telephone number +51 1
572 2539
Fax number +51 1 572 0152
contacto@jwcia.com
www.jwcia.com
- PH Philippines**
Enclosure Systems Specialists
Inc.
2276 Don Chino Roces
Avenue Extension
Room 103/105 Narra Building
1231 Makati City
Telephone number +63 2
813 8580
Fax number +63 2 813 8596
sales_encsys@pltdsl.net
www.enclosuresystemspsh.
com
- PK Pakistan**
Automation Controls (Pak)
Apartment No. 33 C III,
Chenab Block, Allama Iqbal
Town
Lahore
Telephone number +92 42
37809948
Fax number +92 42
37809950
nadeem@acpak.com.pk
www.acpak.com.pk
- PL Poland**
Weidmüller Sp. z. o. o.
ul. Ogrodowa 58
00-876 Warszawa
Telephone number +48 22
510 09 40
Fax number +48 22 510
09 41
biuro@weidmuller.com.pl
www.weidmuller.pl
- PR Puerto Rico**
Please contact
W Interconnections Inc.
United States
- PT Portugal**
Weidmüller Sistemas de
Interface S. A.
Estrada Outeiro Polima, R.
Augusto Dias da Silva, Lote
B - Esct. 2
São Domingos de Rana
2785-515 Abóboda
Telephone number +351 214
459 191
Fax number +351 214
455 871
weidmuller@weidmuller.pt
www.weidmuller.pt
- PY Paraguay**
Please contact
CPI SA
Argentina
- QA Qatar**
Doha Motors
PO Box 145
Telephone number +974
4651441
Fax number +974 4654579
dmtctech@qatar.net.qa
http://www.dohamotorsgroup.
com/td.html
Petroleum Technology Co.
W.L.L.
PO Box 16069
5th Floor Toyota tower
Telephone number +974
44419603
Fax number +974 44419604
petrotec@qatar.net.qa
www.petrotec.com.qa
- RO Romania**
Representative Office
Weidmüller Interface GmbH
& Co. KG
Ionescu Crum Street, No.
1, 1st Tower, 1st Floor,
Office 4
500446 Brasov - Brasov
Business Park
Telephone number +40 (268)
446 222
Fax number +40 (262)
205 410
claudiu.totea@weidmueller.
com
www.weidmueller.com
- RS Serbia**
Representative Office
Weidmüller Interface GmbH
& Co. KG
Ustanicka 189, III sprat
lokal 7a
11050 Beograd
Telephone number +381
112885274
Fax number +381
112885274
zoran.rabrenovic@
weidmueller.com
TeLa Elektrik d.o.o.
Ul. Dr Drage Ljočić 6
Beograd
Telephone number +381 11
2772 415
Fax number +381 11 2772
850
office@tela.rs
www.tela.rs
- RU Russia**
OOO Weidmüller
7/10 Khlebozavodskiy
Passage,
Moskau
115230
Telephone number +7 (495)
771-69-40
Fax number +7 (495) 771-
69-41
Info@weidmueller.ru
www.weidmueller.ru
- SA Saudi Arabia**
Al Abdulkarim Holding Co.
P.O. Box 4
Dammam 31411
Telephone number +966 3
8337110
Fax number +966 3
8829547
E-mail salehsk@akh.com.sa
www.weidmueller.ae
Saudi Electric Supply
Company (SESCO)
P.O. Box 32 98
Al Khobar 31952
Telephone number +966 3
8829546 Ext. 3030
Fax number
www.seesco-gex.com
www.seesco-gex.com
- SE Sweden**
Weidmüller AB
Axel Danielssons väg 271
BOX 31025
SE-200 49 Malmö
Telephone number +46 77-
143 00 44
Fax number +46 40-37 48 60
info@weidmuller.se
www.weidmuller.se
- SG Singapore**
Weidmüller Pte. Ltd.
70 Bendemeer Road
04-03 Luzerne Building
Singapore 339940
Telephone number +65 6841
5311
Fax number +65 6841 5377
info@weidmuller.com.sg
www.weidmuller.com.sg
- SI Slovenia**
Elektrospoji d. o. o.
Stegne 27
SI- 1000 Ljubljana
Osrednjleslovenska
Telephone number +386 1
511 3810
Fax number +386 1 511
1604
info@elektrospoji.si
www.elektrospoji.si
- SK Slovakia**
ELEKTRIS s.r.o.
Elektrárenská 1
831 04 Bratislava
Telephone number +421
2/4920 0113
Fax number +421 2/4920
0119
bratislava@elektris.sk
- SV El Salvador**
Prestegard Electro
11 Avenida Norte No. 240
Edificio Salazar No. 2
San Salvador
Telephone number +503
2271 1690
Fax number +503 2221
3851
prestegard@navegante.com.sv
- SY Syria**
Please contact
Weidmüller Middle East FZE
United Arab Emirates
- SZ Swaziland**
Please contact
Phambili Interface
South Africa

Addresses worldwide

Let's connect.

TH Thailand
Pisanu Engineering Co. Ltd.
Kwang Dingaeng, Khet
Dingaeng
800/2 Soi Trakulsuk, Asoke-
dindaeng Road
Dindaeng, Bangkok
10400
Telephone number +66 2
248 2896
Fax number +662 105 6301
ecsales@pisanu.co.th
www.pisanu.co.th

Representative Office
Weidmüller Pte. Ltd.
37/F, Sathorn Square Building
98 North Sathorn Road
Bangkok, Silom Bangrak
10500
Telephone number +66 2
105 6300
Fax number +66 2 642 9220
info@weidmuller.com.sg

TN Tunisia
Please contact
Weidmüller E. U. R. L.
France

TR Turkey
Weidmüller Elektronik Ticaret
Ltd. Sirketi
Kavacik Mah. Orhan Veli Kanik
Caddesi 9/1
34810 Beykoz / Istanbul
Telephone number +90 (216)
537 10 70
Fax number +90 (216) 537
10 77
info@weidmuller.com.tr
www.weidmuller.com.tr

TW Taiwan
Weidmuller (Hong Kong)
Limited
No. 3, Lane 89, ChungYang
N. Rd
24148 SanChuang City,
Taipei
Telephone number +886 921
949 751
roy.lin@weidmueller.com.hk

TZ Tanzania
Please contact
Phambili Interface
South Africa

UA Ukraine
LLC WM UKRAINE
Levanevskogo str. 6
Kiev
3058
Telephone number +38 044
490 32 48
Fax number
info@wm-ua.com.ua
wm-ua.com.ua/

Representative Office
Weidmueller Interface GmbH
& Co. KG
Z, office 303
7-D, Zdolbunivska str.
Kiev, 2081
Telephone number
(mobile) +38 050 440 25 24
info.ua@weidmueller.com

US United States
W Interconnections Inc.
821 Southlake Boulevard
Richmond Virginia 23236
Telephone number +1 (804)
794-2877
Fax number +1 (804) 379-
2593
info@weidmuller.com
www.weidmuller.com

UY Uruguay
REWO Uruguay S. A.
AV. Bolivia 2001 Esq
Rocafuerte
11300 Carrasco Montevideo
Telephone number +598
2604 8439
Fax number +598 2604
8439
rewo@rewo Uruguay.com.uy

UZ Republic of Uzbekistan
Please contact
OOO Weidmüller
Russia

VE Venezuela
Somerinca C. A.
Corazon de Jesus - 3ra
Transversal con calle el
Carmen- Los Dos Caminos
Caracas 1070-A
Telephone number +58
2122352748
Fax number +58
2122399341
klocmoeller@cantv.net
www.somerinca.com

VN Vietnam
AUMI Industrial Equipment &
Automation Company Limited
E1, La Thanh Hotel
218 Doi Can Street
Lieu Giai Ward, Ba Dinh
District
Hanoi City
Telephone number +84 4
37628601
Fax number +84 4
6266 1391
aumi@aumi.com.vn
www.aumi.com.vn

Representative Office
Weidmüller Pte. Ltd.
Level 16 Saigon Tower
Building
29 Le Duan Street
District 1
Ho Chi Minh
Telephone number +848
3520 7717
Fax number +848 3520
7604
info@weidmuller.com.sg

ZA South Africa
Phambili Interface
PO Box 193
1609 Johannesburg, Edenvale
5 Bundo Road, Sebenza
1610 Johannesburg
Telephone number +27 (11)
4521930
Fax number
info@weidmuller.co.za
www.weidmuller.co.za

Representative Office
Weidmüller Interface GmbH
& Co. KG
210 Amarand
Avenue, Pegasus Building
181 Pretoria, waterkloof Glen
ext 2 -
Telephone number +27 12
003 2906
Fax number +27 (11)
4526455
Jacques.Vosloo@weidmueller.
com
www.weidmueller.com

ZM Zambia
Please contact
Phambili Interface
South Africa

ZW Zimbabwe
Please contact
Phambili Interface
South Africa