

STRIP LED

100922.99



Features

Usage: Interno
Dimming: CON ACCESSORIO
Emergency: CON ACCESSORIO
L: 5000mm
W: 10mm
Warranty: 5 anni
Weight: 0.15kg

Tech Data

IP: 20
Insulation class: III
Power supply voltage: 24 Vdc
SELV: No

Source

LED source: LED
LED power: 8.8W/m
Nominal luminous flux: 902lm
Color temperature: 2700K
CRI: >90
LED lifespan: 30000h L70 B20


Compliance

CEI EN 60598-1:2015 + A11:2009. IEC 60598-2:2015 2-1

Standards

Photobiological risk: Apparecchio certificato in GRUPPO RG1 - Gruppo di Rischio 1 (basso) - Assenza di pericolo dovuta ad una limitazione dell'emissione di radiazione intrinseca al prodotto in conformità alla normativa CEI EN 62471:2010-01, IEC TR 62778:2014.
CAM edilizia: Conforme al CAM EDILIZIA Decreto Ministeriale 11 ottobre 2017.

[View more product info](#)




SMD 3528 (240 LED/m)
Biadesivo - sezionabile ogni 25mm (6 LED)
Biadesive - cuttable every 25mm (6 LED)

STRIP LED


100922.99

EMERGENCY ACCESSORIES



KIT EMERGENZA 1H 9V-58V

18002.99



KIT EMERGENZA 3H 9V-58V

18003.99