

Article code:

5046 644821


EAN:

7021986448214



Light technic

| | |
|-------------------------|-----------------|
| Version: | Sensor |
| Type of light source: | LED |
| Wattage: | 19W |
| System wattage: | 19.0W |
| Luminous flux: | 1225lm |
| Efficacy: | 65 lm/W |
| Voltage: | 230V |
| Colour temperature: | 3000K |
| Colour rendering (CRI): | Ra>80 |
| MacAdams factor: | SDCM: 3 |
| Lifetime: | L70/B50>50,000 |
| Light distribution: | Direct/Indirect |
| Beam angle: | 110° |



Control/Dimming

| | |
|-------|--------|
| Type: | On/Off |
|-------|--------|

Protection

| | |
|----------------------------|-------------|
| Luminaire class: | Class I |
| Ingress protection rating: | IP65 |
| Vandal class: | IK10 |
| Ta nominal: | Ta=25°C |
| Fire protection class: | 850°C - 30s |

Energy and approvals

| | |
|---------------|----|
| Energy class: | A+ |
| Approval: | CE |

Materials and finish

| | |
|----------|-----------------------------|
| Housing: | Aluminium |
| Colour: | Black (RAL 9004) |
| Optics: | UV-stabilized polycarbonate |

Mounting/Connection

| | |
|-----------|---------------------------|
| Mounting: | Surface, Indoor / Outdoor |
| Module: | 2000 |
| Plug: | Screwless terminal block |

Dimensions (mm)

| | |
|------------------------|-----|
| Height (H): | 85 |
| Diameter (D): | 320 |
| Weight (brutto/netto): | 2.3 |

Packaging

| | |
|---------------------|-----------------|
| Packing dimensions: | 340 x 340 x 120 |
|---------------------|-----------------|



7 0 2 1 9 8 6 4 4 8 2 1 4