



HW/FM small distributor JUMBO

Order number: 7250022

Type: JUMBO36+6

Flexible usage. Flush and hollow wall

- Generous wiring space
- Strain relief possible
- Frame height 9 mm
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation

suitable for:

Dimensions

Depth	98 mm
Height	650 mm
Height of HW cut-out	610 mm
Height of mounting recess	643 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	360 mm

Material

Box material	PS
Cover material	PS
Door material	

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	
Insulation	protection class II
Number of compartments	42
Number of rows	3
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

Technical features

Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	
Suitable for sheet thickness	10-45 mm

Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"> • DIN EN 60670-1 • DIN EN 60670-24 • DIN EN 61439-1 • DIN EN 61439-3 • DIN 43871
VDE	true

Accessories

Equipped with	1x door with frame (T+RJUMBO36+6) 1x PE plug-in terminal (SKPE34) 1x N plug-in terminal (SKN34) 1x N-N plug-in terminal (SKN17N)
Recommended purchase	