



WEVER & DUCRÉ
LIGHTING

DEEPER 1.0 MR16

152110S0

Project

Type

Notities

Kwantiteit

Datum

ALGEMEEN

Plafond

Ingebouwd

Wit aluminium

RAL 9006^a

IP20

Interieur

LED

Lamp QR-CBC51

MR16

Socket GU5.3

max. 12.0 W

OPTISCH

Downlight

ELEKTRISCH

excl. driver

12 V

Klasse 3

Veiligheidsafstand 0.3 m

FYSISCH

Diameter 84 mm

Height 96 mm

0.1 kg

CUTOUT


Diameter 76-79 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 38 mm

Recessed depth 100 mm

^a Color may deviate slightly due to production conditions.



Ronde downlight van gegoten aluminium, voor plafondbouw; RAL 9006; gereedschapsloze installatie met draadveren; geschikt voor plafonddikte van 4-38 mm; inbouwdiepte 100 mm; lampfitting GU5.3; lamp-type QR-CBC51; max. 12W; 12 V; beschermingsgraad IP20; PC3; driver niet inbegrepen; lamp niet inbegrepen;





WEVER & DUCRÉ
LIGHTING

DEEPER 1.0 MR16

152110S0

ELEKTRISCH

Driver

TYPE	L · W · H (MM)	ORDERCODE
10W 12V	102-51-30	9 0 2 2 1 4 0 1
25W 12V	145-51-29.5	9 0 2 2 1 7 0 1
70W 12V	108-52-33	9 0 2 2 1 9 0 4