

PRODUCT DATASHEET LEDinestra 25 200° 3.5 W/827 S14s

LEDinestra | Tubular LED lamps



AREAS OF APPLICATION

- Ideal for mirror lighting
- Hotels, restaurants
- Domestic applications
- Outdoor applications only in suitable luminaires

PRODUCT BENEFITS

- Long lifetime of up to 15,000 h
- Low energy consumption
- Good color rendering

PRODUCT FEATURES

- LED alternative to tubular incandescent lamps
- Uniform illumination
- Mercury-free lamps
- Made in Germany



TECHNICAL DATA

Electrical data

Rated wattage	3.50 W
Nominal wattage	3.50 W
Nominal voltage	220240 V
Operating frequency	5060 Hz
Claimed equiv. conventional lamp power	25 W

Photometrical data

Rated color temperature	2700 K	
Color rendering index Ra	>80	
Lumen main.fact.at end of nom.life time	0.70	
Light color (designation)	Warm White	
Nominal luminous flux	260 lm	

Dimensions & weight



Overall length	300.0 mm			
Lifespan				
Nominal lamp life time	15000 h			
Rated lamp life time	15000 h			
Number of switching cycles	100000			
Additional product data				
Base (standard designation)	S14s			
Mercury-free	Yes			
Capabilities Capabilities				
Dimmable	No	·		

Country specific categorizations

ILCOS	DRL/F-3,5/827-230-S14S-29/300	
Order reference	LEDINESTRA25 3,	

LOGISTICAL DATA

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4058075817739	LEDinestra 25 200° 3.5 W/827 S14s	Shipping carton box 10	370 mm x 215 mm x 155 mm	12.33 dm³	1055.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

REFERENCES / LINKS

For further products and actual information concerning LED lamps see

www.ledvance.com/ledlamps

For Guarantee see

www.ledvance.com/guarantee

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.