

**K72 IP54 LED TRE DIM RG**


K already earned its spurs in the Modular range. With the LED dedicated rework of the K we honour an icon. A timeless product that will remain in the Modular portfolio for many years to come. Suitable for general and accent lighting, K is available in donkey grey and white structure.

Art. Nr. 14041409

**SPECIFICATIONS**

Lamp	1x LED Array 9.2W
Gear / Transfo	LED gear incl.
Cut-out size	ø 65 h 60
Weight	0.29kg
Min. Distance	0.1
Power supply	230V
IP	IP54
Glow Wire Test	960°
CRI	90
Lumen	739 Lm
Efficacy	62 Lm/W
UGR	21
Adjustability	Not Applicable
Remark	! 3500K on request

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
donkey grey struc	14041071	14041171	14041271	14041371	14041471	14041571	14041671	14041771	14041871
white struc	14041009	14041109	14041209	14041309	<b>14041409</b>	14041509	14041609	14041709	14041809



This label is available in other languages:  
<http://supermodular.com/assets/TYPE2.pdf>



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on [www.supermodular.com](http://www.supermodular.com).

## K72 IP54 LED TRE DIM RG

### ACCESSORIES

#### CONBOX

10490330 | CONBOX 112X172X100X236

