



WEVER & DUCRÉ
LIGHTING

DEEP 1.0 MR16

112110B0

Project

Type

Notities

Kwantiteit

Datum

ALGEMEEN

Plafond

Ingebouwd

Matzwart

RAL 9011^a

IP20

Interieur

LED

Lamp QR-CBC51

MR16

Socket GU5.3

max. 12.0 W

ELEKTRISCH

excl. driver

12 V

Klasse 3

Veiligheidsafstand 0.3 m

FYSISCH

Diameter 84 mm

Height 76 mm

0.3 kg

draadveren

CUTOUT


Diameter 76-79 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 27 mm

Recessed depth 90 mm

^a Color may deviate slightly due to production conditions.



Ronde downlight van gegoten aluminium, voor plafondinbouw; oppervlak Matzwart; gepoedercoat; mat textuur; RAL 9011; gereedschapsloze installatie met behulp van draadveren; inbouwdiepte 90 mm; lampfitting GU5.3; lamptype QR-CBC51; max. 12W; 12 V; beschermingsgraad IP20; PC3; driver niet inbegrepen; lamp niet inbegrepen;





WEVER & DUCRÉ
LIGHTING

DEEP 1.0 MR16

112110B0

ELEKTRISCH

Driver

TYPE	L · W · H (MM)	ORDERCODE
10W 12V	102-51-30	9 0 2 2 1 4 0 1
25W 12V	145-51-29.5	9 0 2 2 1 7 0 1
70W 12V	108-52-33	9 0 2 2 1 9 0 4