



M-LED 70 GE

With the introduction of the in-house developed M-LED modules, we are preparing some of our icons for the future. The M-LED 111 module is replacing the AR111 lamp and comes in white structure or black matt. M-LED 111 is applicable for following 'AR111' (GE) luminaires: Bolster recessed, Nomad, Multiple, Multiple trimless, Lotis, Haloscan and Thub metal. Also fits AR111 modules of SL149, Multiple(x), Freeway, 2FLAT2C and Traffic. M-LED 70 is replacing the well-known AR70 lamp. The M-LED 70 module is applicable for 'AR70' luminaires such as Mini multiple and Haloscan 128.

Art. Nr. 14070602

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Weight	0.18kg	
Min. Distance		
IP	IP20	
Glow Wire Test	960°	
CRI	90	
Power supply	350mA 17.8Vf	500mA 18.4Vf
Connected load	6.2W	9.2W
Lumen	649lm	871lm
Efficacy	105lm/W	95lm/W
UGR	21	22
Adjustability	Not Applicable	
Remark	! 3500K on request	

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black	14070002	14070102	14070202	14070302	14070402	14070502	14070602	14070702	14070802
white struc	14070009	14070109	14070209	14070309	14070409	14070509	14070609	14070709	14070809

