

WINK ASY 115 LED GE


Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon.

Art. Nr. 13071732

SPECIFICATIONS

Lamp	1x LED Array			
Gear / Transfo	LED gear not incl.			
Cut-out size	ø 146 h 100			
Weight	0.87kg			
Min. Distance	0.1m			
IP	IP54			
Glow Wire Test	960°			
CRI	90			
Power supply	350mA 29.1Vf	500mA 29.9Vf	700mA 31Vf	900mA 31.7Vf
Connected load	11W	16.2W	23.4W	31W
Lumen	764lm	1007lm	1263lm	1448lm
Efficacy	69lm/W	63lm/W	55lm/W	47lm/W
UGR	18	19	20	20
Adjustability	h 355°			
Remark	! 3500K and 4000K on request			

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	13071032	13071332	13071632	13071132	13071432	13071732
white struc	13071009	13071309	13071609	13071109	13071409	13071709



This label is available in other languages:
<http://supermodular.com/assets/TYPE2.pdf>

