

**K72 IP54 LED GE**


K already earned its spurs in the Modular range. With the LED dedicated rework of the K we honour an icon. A timeless product that will remain in the Modular portfolio for many years to come. Suitable for general and accent lighting, K is available in donkey grey and white structure.

Art. Nr. 14040009

**SPECIFICATIONS**

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 65 h 60	
Weight	0.19kg	
Min. Distance	0.1	
IP	IP54	
Glow Wire Test	960°	
CRI	90	
Power supply	350	<b>500</b>
	17.8	<b>18.4</b>
Connected load	6.2W	<b>9.2W</b>
Lumen	519lm	<b>667lm</b>
Efficacy	84lm/W	<b>73lm/W</b>
UGR	20	<b>21</b>
Adjustability	Not Applicable	
Remark	! 3500K on request	

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
donkey grey struc	14040071	14040171	14040271	14040371	14040471	14040571	14040671	14040771	14040871
white struc	<b>14040009</b>	14040109	14040209	14040309	14040409	14040509	14040609	14040709	14040809



This label is available in other languages:  
<http://supermodular.com/assets/TYPE2.pdf>



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on [www.supermodular.com](http://www.supermodular.com).

## K72 IP54 LED GE

### ACCESSORIES

#### CONBOX

10490330 | CONBOX 112X172X100X236

#### DRIVER-LED

12403730 | LED GEAR 350MA 15W

