

# Jupiter, Tellus, Polar, 230V



230V, 50Hz, max 50W, GU10, Class II, IP23\*

● 0,5 - 1,0 mm<sup>2</sup> 8 mm

● 1,5 - 2,5 mm<sup>2</sup> 12 mm

ca 10° (max. 20°)

Max 16A

Halogen

7W LED

		h (min.) (mm)	Ø (mm)
Jupiter	230 V	110	84
Jupiter	LED 230 V		
Jupiter	Exclusive 230 V		
Jupiter	Exclusive LED 230 V		
Jupiter	Soft 230 V		
Jupiter	Soft LED 230 V	135	
Jupiter	Outdoor 230 V		
Jupiter	Outdoor LED 230 V	110	
Tellus	230 V		
Tellus	LED 230 V		
Tellus	Exclusive 230 V	130	
Tellus	Exclusive LED 230 V		
Polar	230 V	110	72

NO: Minimumsavstand til brennbart materiale i armaturens stråleretning.

EN: Minimum distance to flammable material in the beam direction.

FR: Distance minimum entre le faisceau lumineux de l'armature et toute matière inflammable.

NL: Minimale afstand tussen de lichtstraal van de armatuur en het brandbaar materiaal.

DE: Der kleinste Abstand zum brennbaren Material in die Richtung des Lichtstrahls.

SG Multibox

SG Downlightbox

SG Sealbox & Frame

Rev. 01.06.2011

SG Armaturen AS  
Svaabekk Industriområde  
N-4790 Lillesand  
NORGE  
Tel: +47 37 26 84 84  
www.sg-as.no

SG Armaturen AB  
August Barksg. 30B  
SE-421 32 Västra Frölunda  
SVERIGE  
Tel: +46 31 81 71 10  
www.sg-ab.se

SG Lighting SA/NV  
Wayenborgstraat 4  
B-2800 Mechelen Noord II  
BELGIQUE/BELGIË  
Tel: +32 (0) 15 20 72 71  
www.sglighting.net

SG Lighting SA/NV  
Parc de l'Arboretum  
73 rue de Saint Mandrier  
83140 Six Fours Les Plages  
FRANCE  
Tel: +33 04 94 93 00 00  
www.sglighting.net

SG Leuchten GmbH  
Nordstrasse 53  
D-59399 Olfen  
DEUTSCHLAND  
Tel: 0152-57000500  
www.sg-leuchten.de