





ENTERO RD-S TRIMLESS TW 94045 W

28464 9030 W

BESCHIKBAAR IN
ZWART 28464 9030 B
GOUD KLEUR 28464 9030 GC
WIT 28464 9030 W



[Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - Ø KIT
INBOUWDIEPTE (MM)	105
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.235
RICHTBAARHEID	0° tot 30° zwenkbaar, 355° roteerbaar
INFO	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8) Optional REFLECTOR 20° available

Elektrische info

KLASSE	III
ENERGIE KLASSE	E

Info lichtbron

Lightsource Name	LED
Lichtbron	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30-15 Waarden	Rf: 89 / Rg: 100
SDCM	SDCM2
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	979lm // 9W // 109lm/W
LED techniek (toestel)	751lm // 10W // 73lm/W

Benodigheden

MOUNTING KIT ENTERO ROUND S
MOUNTING KIT AIR 105
LED POWER SUPPLY 500mA-DC TW

ENTERO RD-S TRIMLESS TW 94045 W











28464 9030 W

Accessoires

ENTERO S HONEYCOMB
 ENTERO S LINEAR SPREAD LENS
 ENTERO S SPREAD LENS
 ENTERO S SOFTENING LENS
 ENTERO S GLASS SBL

Voor gedetailleerde montage gegevens, consulteer de handleiding: [28464_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Plasterboard	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stucanet	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Wood	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT ENTERO RD-S O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT ENTERO RD-S CSC	Required
	 MOUNTING KIT ENTERO RD-S WSC	Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR ONLY 1	Required
	 MOUNTING KIT SIDE AIR 105	Required
	 MOUNTING KIT NO AIR 105	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 105	Required
	 MOUNTING KIT TOP AIR 105	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required


ENTERO RD-S TRIMLESS TW 94045 W

28464 9030 W

VERVOLLEDIG UW SPECIFICATIE

LED voedingen

#




21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5

1->2

Montage kit




28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.



28500 0220 MOUNTING KIT DEEP ENTERO RD-S TRIMLESS

Montage kit spanplafond




28400 0070 MOUNTING KIT ENTERO RD-S CSC



28400 0130 MOUNTING KIT ENTERO RD-S WSC

Montage kit - side air + light




29810 0110 MOUNTING KIT SIDE AIR 105

ENTERO RD-S TRIMLESS TW 94045 W

28464 9030 W


Montage kit - top air + light



29810 0130 MOUNTING KIT TOP AIR 105




Montage kit - side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1



Montage kit - top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1



Montage kit - no air



29810 0120 MOUNTING KIT NO AIR 105



ENTERO RD-S TRIMLESS TW 94045 W

28464 9030 W

Light veranderende onderdelen




28500 0010 ENTERO S LINEAR SPREAD LENS




28500 0020 ENTERO S SPREAD LENS




28500 0030 ENTERO S SOFTENING LENS



28500 0040 ENTERO S GLASS SBL



28500 0050 B ENTERO S HONEYCOMB SINGLE USE B



28500 0060 B ENTERO S HONEYCOMB DOUBLE USE B

Notes: