



WEVER & DUCRÉ
LIGHTING

TAIO ROUND IP65 1.0

180181G5

Project

Type

Notities

Kwantiteit

Datum

ALGEMEEN

Plafond

Ingebouwd

Goud

IP65

Interieur

335^a tot 455^b lm

LED

3000 K

OPTISCH

Flood

ELEKTRISCH

excl. driver

18 V

LED inset 6.0^a tot 9.0^b W

350 tot 500 mA

Klasse 3

Veiligheidsafstand 0.3 m

FYSISCH

Diameter 77 mm

Height 55 mm

0.1 kg

draadveren

CUTOUT

Diameter 70 mm

Min. ceiling thickness 4 mm

Max. ceiling thickness 27 mm

Recessed depth 70 mm


^a 350mA

^b 500mA



IP65   

Ronde downlight van gegoten aluminium, voor inbouw in het plafond, met opaalglazen lens; oppervlak Goud; gepoedercoat; mat textuur; gereedschapsloze installatie met behulp van draadveren; geschikt voor plafonddikte van 4-27 mm; inbouwdiepte 70 mm; met COB (Chip on Board) technologie voor maximale efficiëntie; lichtkleur 3000 K; CRI (Colour Rendering Index) \geq 90; beschermingsgraad IP65; PC3; IC-waarde; driver niet inbegrepen;





WEVER & DUCRÉ
LIGHTING

TAIO ROUND IP65 1.0

180181G5

ELEKTRISCH

Driver

TYPE	L · W · H (MM)	SPANNING	ORDERCODE
10W 500mA 11-20V	100·43·23	11 - 20V	9 0 2 1 4 4 0 5
24W 500mA 2-49V IP68	122·54·26		9 0 2 1 4 7 0 2
10W 500mA 3-20V	102·49·29		9 0 2 2 4 4 0 2
10W 500mA 10-20V	102·51·30	11 - 20V	9 0 2 3 4 4 0 1
17W 350mA 10-49V	108·52·22		9 0 2 4 3 6 0 1
10W 500mA 2.5-20V	124·31·21	2.5 - 20V	9 0 2 4 4 4 0 1