



WEVER & DUCRÉ  
LIGHTING

# DEEP IP44 1.0 MR16

112610B0C

Project

Type

Notities

Kwantiteit

Datum

## ALGEMEEN

Plafond

Ingebouwd

Matzwart

RAL 9011<sup>a</sup>

Front IP44

Back IP20

Interieur

## LED

Lamp QR-CBC51

MR16

Socket GU5.3

max. 12.0 W

## ELEKTRISCH

excl. driver

12 V

Klasse 3

Veiligheidsafstand 0.3 m

## FYSISCH

Diameter 95 mm

Height 86 mm

0.3 kg

bladveren

## CUTOUT

Diameter 86-89 mm


Min. ceiling thickness 8 mm

Recessed depth 90 mm

<sup>a</sup> Color may deviate slightly due to production conditions.



Ronde downlight van gegoten aluminium, voor plafondbouw; oppervlak Matzwart; gepoedercoat; mat textuur; RAL 9011; gereedschapsloze installatie met behulp van bladveren; inbouwdiepte 90 mm; lampfitting GU5.3; lamptype QR-CBC51; max. 12W; 12 V; beschermingsgraad IP44; PC3; driver niet inbegrepen; lamp niet inbegrepen;





WEVER & DUCRÉ  
LIGHTING

# DEEP IP44 1.0 MR16

112610B0C

## ELEKTRISCH

### Driver

TYPE	L · W · H (MM)	ORDERCODE
10W   12V	102-51-30	9 0 2 2 1 4 0 1
25W   12V	145-51-29.5	9 0 2 2 1 7 0 1
70W   12V	108-52-33	9 0 2 2 1 9 0 4