









Data Sheet | Item Number: 887-931
Splicing Connector Set; L-BOXX® 102; 221 Series - 4mm² and 6mm²



<https://www.wago.com/887-931>



This item includes:

 Item No.: 221-412 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-413 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-415 COMPACT Splicing Connector; for all conductor types; max. 4 mm ² ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm ² ; transparent	 Item No.: 221-500 2 Mounting carrier; 221 Series - 4 mm ² ; for DIN-35 rail mounting/screw mounting; orange
 Item No.: 221-612 COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm ² ; transparent	 Item No.: 221-613 COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm ² ; transparent	 Item No.: 221-615 COMPACT Splicing Connector; for all conductor types; max. 6 mm ² ; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm ² ; transparent	 Item No.: 221-510 2 Mounting carrier; 221 Series - 6 mm ² ; for DIN-35 rail mounting/screw mounting; orange

Material Data

Note (material data)

[Information on material specifications can be found here](#)

Fire load	29.162 MJ
Weight	3684.1 g

Commercial data

ETIM 8.0	EC000446
ETIM 7.0	EC000446
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055144079166
Customs tariff number	85369010000

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com