





WINK ASY 115 LED GE

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon.

| Art. Nr. 13071132 | | | | |
|-------------------|-----|----|------|-------|
| | Δrt | Nr | 1307 | 71122 |

SPECIFICATIONS

| Lamp | 1x LED Arra | ıy | | | | | |
|----------------|--------------------|--------|--------|--------|--|--|--|
| Gear / Transfo | LED gear not incl. | | | | | | |
| Cut-out size | ø 146 h 100 | | | | | | |
| Weight | 0.87kg | | | | | | |
| Min. Distance | 0.1m | | | | | | |
| IP | IP54 | | | | | | |
| Glow Wire Test | 960° | | | | | | |
| CRI | 90 | | | | | | |
| Power supply | 350mA | 500m A | 700mA | 900mA | | | |
| | 29.1Vf | 29.9Vf | 31Vf | 31.7Vf | | | |
| Connected load | 11W | 16.2W | 23.4W | 31W | | | |
| Lumen | 799lm | 1053Im | 1321lm | 1513lm | | | |
| Efficacy | 73lm/W | 66lm/W | 57lm/W | 49lm/W | | | |
| UGR | 17 | 17 | 18 | 19 | | | |
| Adjustability | h 355° | | | | | | |

Remark ! 3500K and 4000K on request



This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf

| | WARM WHITE 2700K / CRI 90+ | | | WARM WHITE 3000K / CRI 90+ | | |
|-------------|-------------------------------|---------------|--------------|-------------------------------|---------------|--------------|
| | SPOT 15° | MEDIUM 25° | FLOOD 40° | SPOT 15° | MEDIUM 25° | FLOOD 40° |
| black struc | 13071032 | 13071332 | 13071632 | 13071132 | 13071432 | 13071732 |
| white struc | 13071009 | 13071309 | 13071609 | 13071109 | 13071409 | 13071709 |











