



Colour Box



395 x 290 x 90 mm



3740 g

EAN Barcode 5411857320794

FR	Projecteur LED	NL	LED Flood spot	GB	LED Flood spot
<p><b>Caractéristiques :</b></p> <p>Type : Premium Line</p> <p>Boîtier en aluminium coulé</p> <p>Alimentation 230 V~ 50 Hz</p> <p>Module LED 100W Epistar SMD2835 leds</p> <p>Angle horizontal : 120 °</p> <p>Angle vertical : 120 °</p> <p>Rendement lumineux : 120 lm / W</p> <p>Puissance lumineuse : 12000 lm</p> <p>Couleur : 4000 K (blanc froid)</p> <p>Indice de protection : IP65</p> <p>Durée de vie : 35.000 h</p> <p>Dimensions : 300 x 291 x 45 mm</p> <p>Classe de consommation : A</p> <p>Consommation : 100 kWh/1000 h</p> <p>CRI : &gt; 80</p> <p>ERP Startup : &lt; 1 sec</p> <p>ERP Warm up 60% : &lt; 1 sec</p> <p>ERP Mercury rate : &lt; 0%</p> <p>Equipé d'un câble de 1 m H07RNF 3G1.00mm<sup>2</sup> VDE</p> <p>Sous réserve de modifications sans avis préalable</p>		<p><b>Eigenschappen :</b></p> <p>Type : Premium Line</p> <p>Die-cast aluminium behuizing</p> <p>Voeding 230 V~ 50 Hz</p> <p>Module LED 100W Epistar SMD2835 leds</p> <p>Horizontale hoek : 120 °</p> <p>Verticale hoek : 120 °</p> <p>Lichtopbrengst : 120 lm / W</p> <p>Lichtsterkte : 12000 lm</p> <p>Kleur : 4000 K (koud wit)</p> <p>Waterdichtheid : IP65</p> <p>Levensduur : 35.000 h</p> <p>Afmetingen : 300 x 291 x 45 mm</p> <p>Verbruiksklasse : A</p> <p>Verbuik : 100 kWh/1000 h</p> <p>CRI : &gt; 80</p> <p>EUP Startup : &lt; 1 sec</p> <p>EUP Warm up 60% : &lt; 1 sec</p> <p>EUP Mercury rate : &lt; 0%</p> <p>Uitgerust met 1 m kabel H07RNF 3G1.00mm<sup>2</sup> VDE</p> <p>Onder voorbehoud van wijzigingen zonder voorafgaand bericht</p>		<p><b>Features :</b></p> <p>Type : Premium Line</p> <p>Die-cast aluminium housing</p> <p>Power 230 V~ 50 Hz</p> <p>Module LED 100W Epistar SMD2835 leds</p> <p>Horizontal angle : 120 °</p> <p>Vertical angle : 120 °</p> <p>Light efficiency : 120 lm / W</p> <p>Light power : 12000 lm</p> <p>Colour : 4000 K (cool white)</p> <p>Protection : IP65</p> <p>Lifetime : 35.000 h</p> <p>Dimensions : 300 x 291 x 45 mm</p> <p>Consumption class : A</p> <p>Consumption : 100 kWh/1000 h</p> <p>CRI : &gt; 80</p> <p>EUP Startup : &lt; 1 sec</p> <p>EUP Warm up 60% : &lt; 1 sec</p> <p>EUP Mercury rate : &lt; 0%</p> <p>Supplied with 1 m cable H07RNF 3G1.00mm<sup>2</sup> VDE</p> <p>Features are subject to change without prior notice</p>	