





WINK ASY 115 LED GE

Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon.

Δrt	Nr	130	71309

SPECIFICATIONS

Lamp	1x LED Array						
Gear / Transfo	LED gear not incl.						
Cut-out size	ø 146 h 100						
Weight	0.87kg						
Min. Distance	0.1m						
IP	IP54						
Glow Wire Test	960°						
CRI	90						
Power supply	350mA	500mA	700mA	900mA			
	29.1Vf	29.9Vf	31Vf	31.7Vf			
Connected load	11W	16.2W	23.4W	31W			
Lumen	776lm	10231m	1283lm	1469lm			
Efficacy	71lm/W	64lm/W	56lm/W	47lm/W			
UGR	17	18	18	19			
Adjustability	h 355°						

! 3500K and 4000K on request



This label is available in other languages: http://supermodular.com/assets/TYPE2.pdf

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	13071032	13071332	13071632	13071132	13071432	13071732
white struc	13071009	13071309	13071609	13071109	13071409	13071709











