

PRODUCT DATA SHEET

Part number 361

EAN 4015609000524

Manufacturer WALTHER-WERKE

WEEE-Reg.-Number: DE 22131895

Product description

Coupler 63A 5P 6h with cable gland



Similar image

Detailed product description

WALTHER Coupler 63A 5P 400V 6h IP44

made from PA6 material

with screw terminal

and cable gland




Increased safety due to injected 2K seal

and two contact screws.

Ordering Information

| | |
|-------------------------|-----------|
| Order unit | Piece |
| Customs number | 85366990 |
| Net weight | 0,7654 kg |
| Packing quantity (VPE) | 5 |
| Length of the packaging | 0,31 m |
| Width of the packaging | 0,255 m |
| Depth of the packaging | 0,15 m |
| Gross weight(VPE) | 4,023 kg |

Certificates

| | | |
|-------------------|-----------------------|---|
| VDE certification | 40000699 |  |
| UL certification | No. E329476 |  |
| EAC certification | BY112.02.01.020 06101 |  |



Classification system

| | |
|-----------------------|----------|
| Classification system | ETIM_6.0 |
| ETIM Class | EC001320 |

Technical product data

| | |
|---------------------------------------|----------------------|
| IEC-amperage | 63 A |
| Amperage acc. UL/CSA (for UL-version) | 60 A |
| Number of poles | 5 |
| Voltage acc. EN 60309-2 | 400 V (50+60 Hz) red |
| Clock hour position | 6 h |
| Identification colour | Red |
| RAL-number | 3000 |
| Degree of protection (IP) | IP44 |
| Connection system | Screwed terminal |
| Angle of plug | Straight |
| Cable entry | Swivel |
| Material | Plastic |

Dimension sheet



| Amp. | 16 | | | 32 | | | 63 | | |
|------|----------|----------|----------|---------|---------|---------|---------|---------|---------|
| Pole | 3 | 4 | 5 | 3 | 4 | 5 | 3 | 4 | 5 |
| d | 135 | 151 | 151 | 171 | 171 | 171 | 255 | 255 | 255 |
| Øe | 51 | 65 | 65 | 72 | 72 | 72 | 96 | 96 | 96 |
| f | 68 | 85 | 85 | 91 | 91 | 98 | 114 | 114 | 114 |
| m | 110 | 113 | 113 | 136 | 136 | 136 | 194 | 194 | 194 |
| Øp | 7,5-14,5 | 7,5-14,5 | 7,5-14,5 | 10-19,5 | 10-19,5 | 10-19,5 | 18-34,5 | 18-34,5 | 18-34,5 |