

Data Sheet | Item Number: 887-928
Splicing Connector Set; L-BOXX® 102; 221 Series - 4mm² and 6mm²



<https://www.wago.com/887-928>



This item includes:



Item No.: 221-412

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 2-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 221-413

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 3-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 221-415

COMPACT Splicing Connector; for all conductor types; max. 4 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 4,00 mm²; transparent



Item No.: 221-500

Mounting carrier; 221 Series - 4 mm²; for DIN-35 rail mounting/screw mounting; orange

10



Item No.: 221-615

COMPACT Splicing Connector; for all conductor types; max. 6 mm²; 5-conductor; with levers; transparent housing; Surrounding air temperature: max 85°C (T85); 6,00 mm²; transparent

30

Material Data

Note (material data)

[Information on material specifications can be found here](#)

Fire load	28.255 MJ
Weight	3553.1 g

Commercial data

ETIM 8.0	EC000446
ETIM 7.0	EC000446
PU (SPU)	1 pcs
Packaging type	Box
Country of origin	DE
GTIN	4055144078961
Customs tariff number	85369010000

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: www.wago.com