



 PRODUCT-DETAILS

UK648N3

Consumer unit , Flush-/ hollow wall mounting, 48 modules, 4 row(s), IP30, Door: Enkele deur, Steel Sheet, Dimensions: 747 mm x 384 mm x 97 mm



Algemene informatie

Type	UK648N3
Artikelnummer	2CPX031372R9999
EAN	4011617313724
Omschrijving	Consumer unit , Flush-/ hollow wall mounting, 48 modules, 4 row(s), IP30, Door: Enkele deur, Steel Sheet, Dimensions: 747 mm x 384 mm x 97 mm
Lange omschrijving	Consumer unit, series UK600, Expansion option: Lateral and bottom, for the internal use, with closed doorframe and door, class of protection II (double insulated), degree of protection IP30, applicable standards: EN 60670-24, Impact strength IK07, Rated operational voltage 400V AC 50/60 Hz, rated current 63 A, Glow wire resistance 850°C, Powder-coated, in RAL 9016, enclosure out of thermoplast, with trim frame and metal door, door out of sheet steel, in RAL 9016, with TIP-in closure, door opening angle 120 degree, door hinge right or left, cable entry on top via cable entry slide part is pre-punched, on bottom via cable entry slide part is pre-punched, on side via pre-punched, rear wall pre-punched, dimensions in mm (H x W x D): 747 x 384 x 97, Shutter frame dimensions in mm (H x W x D): 747 x 384 x 9, Space units 48, Row distance in mm: 125, covers out of Plastic, 90 degree press and turn closure, with N/PE Quick-terminal, cable fastening rail integrated, assembled with device carrier, device support removable

Technische specificaties

Nominaal bedrijfsvoltage	Maximum 400 V
Operationeel voltage	400 V
Toegekende stroom (I_n)	63 A
Vermogensverlies	$\Delta t = 30K$ 62 W
Aantal fasen	4
Aantal rijen	4
Type sluiting	Push Button
Configuratietype	assembled with device carrier
Afdekplaattype	Door
Behuizingstype	Consumer unit
Montagetype	Flush-/ hollow wall mounting
Deurtype	Enkele deur
Uitvoering oppervlakte	Powder-coated
Materiaal behuizing	Plastic
Accessoires beschikbaar	Ja
Afdekestijl	Closed
DIN-plaatseenheden	48
RAL-nummer	RAL 9016 - Verkeerswit
Kleur	Traffic white
Terminaltype	Quick-Terminal

Material Compliance

RoHS-informatie	2CPC100018X0201
RoHS-status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS-datum	20240903
REACH-verklaring	2CPC100005X0201
REACH Information	False - does not contain substances > 0.1 mass percentage
REACH Date	20240902
Rapport over conflictmineralen (CMRT)	9AKK108468A3363

Milieu

Beschermingsgraad	IP30
Beschermingsklasse	Geïsoleerd

Afmetingen

Breedte in module-eenheden	12
Product netto breedte	384 mm
Product netto hoogte	747 mm
Product netto diepte	97 mm
Product netto gewicht	5.026 kg
Inbouwdiepte (t_2)	88 mm
Dimensiediagram	2CPC000001D0201 2CPC000002D0201 2CPC000007D0201

Verpakkingsinformatie

Pakketniveau 1 Units	pack 1 stuk
Pakketniveau 1 Breedte	390 mm
Pakketniveau 1 Hoogte	756 mm
Pakketniveau 1 Lengte	115 mm
Pakketniveau 1 Brutogewicht	5.227 kg
Pakketniveau 1 EAN	4011617313724
Pakketniveau 2 Units	pallet (lift) 45 stuk
Pakketniveau 2 Breedte	800 mm
Pakketniveau 2 Hoogte	1820 mm
Pakketniveau 2 Lengte	1200 mm
Pakketniveau 2 Brutogewicht	246.17 kg

Bestelinformatie

Minimale bestelhoeveelheid	1 stuk
E-Number (Sweden)	2201242

Certificaten en verklaringen (documentnummer)

Conformiteitsverklaring - CE	2CPC100018X0201
---------------------------------	-----------------

Installation

Instructies en handleidingen	2CPC129380M5601
---------------------------------	-----------------

Populaire downloads

Gegevensblad, technische informatie	2CPC000001C0101 2CPC000002C0101
Building Information Modeling – BIM	9AKK107046A7947

Externe classificaties en normen

ETIM 8	EC000214 - Installatiekast met DIN-rail leeg
ETIM 9	EC000214 - Installatiekast met DIN-rail leeg
WEEE-categorie	4. Large Equipment (Any External Dimension More Than 50 cm)
AEEA B2C / B2B	Business To Consumer
CN8	85381000
eClass	V11.0 : 27142409
Object classificatiecode	U
Normen	DIN 43871

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
2CPX031434R9999	Enclosure accessories , Dimensions: 80 mm x 120 mm x 30 mm	UZ91P4	1	piece
2CPX062745R9999	Quick terminals terminals , blue , N/RDC Terminal , Quick-Terminal	ZK50BT	1	piece
2CPX030892R9999	Enclosure accessories , Direct mounting, IP30, Dimensions: 36 mm x 42 mm x 15 mm	ZK507	1	piece
2CPX031413R9999	Enclosure accessories , Door: Enkele deur, Dimensions: 43 mm x 59 mm x 41 mm	UZT4	1	piece
2CPX031412R9999	Enclosure accessories , Door: Enkele deur, Dimensions: 43 mm x 59 mm x 41 mm	UZT3	1	piece
2CPX031787R9999	Enclosure accessories , Stones Foil, Dimensions: 833 mm x 347 mm x 1 mm	UZ641D	1	piece
2CPX031405R9999	Enclosure accessories , 48 modules, 4 row(s), Dimensions: 747 mm x 384 mm x 90 mm	AP648	1	piece
2CPX031786R9999	Enclosure accessories , Memory Board Foil, Dimensions: 833 mm x 347 mm x 1 mm	UZ640D	1	piece
2CPX061178R9999	Interior fitting system , Dimensions: 62 mm x 125 mm x 68 mm	ZX29	1	piece
2CPX061177R9999	Customized electrical components , Dimensions: 50 mm x 102 mm x 63 mm	ZE225	1	piece
2CPX031408R9999	Enclosure accessories , Dimensions: 109 mm x 109 mm x 36 mm	UZB2	1	piece
2CPX061211R9999	Customized electrical components , Dimensions: 63 mm x 213 mm x 58 mm	ZE227	1	piece
2CPX031788R9999	Enclosure accessories , Wood Foil, Dimensions: 833 mm x 347 mm x 1 mm	UZ642D	1	piece
2CPX031789R9999	Enclosure accessories , Drops Foil, Dimensions: 833 mm x 347 mm x 1 mm	UZ643D	1	piece
2CPX031427R9999	Customized electrical components , Dimensions: 54 mm x 50 mm x 58 mm	ZE224	1	piece
2CPX031409R9999	Enclosure accessories , Dimensions: 68 mm x 294 mm x 30 mm	UZB3	1	piece

Categorieën

Laagspanningsproducten en -systemen → Verdelers → Installatiekasten (System pro E comfort) → Installatiekasten → UK600

