



WEVER & DUCRÉ  
LIGHTING

# DEEP 1.0 MR16

112110W0

Project

Type

Notities

Kwantiteit

Datum

## ALGEMEEN

Plafond

Ingebouwd

Matwit

RAL 9003<sup>a</sup>

IP20

Interieur

## LED

Lamp QR-CBC51

MR16

Socket GU5.3

max. 12.0 W

## ELEKTRISCH

excl. driver

12 V

Klasse 3

Veiligheidsafstand 0.3 m

## FYSISCH

Diameter 84 mm

Height 76 mm

0.3 kg

draadveren

## CUTOUT


Diameter 76-79 mm

Min. ceiling thickness 4 mm


Max. ceiling thickness 27 mm

Recessed depth 90 mm

<sup>a</sup> Color may deviate slightly due to production conditions.



Ronde downlight van gegoten aluminium, voor plafondbouw; oppervlak Matwit; gepoedercoat; mat textuur; RAL 9003; gereedschapsloze installatie met behulp van draadveren; inbouwdiepte 90 mm; lampfitting GU5.3; lamptype QR-CBC51; max. 12W; 12 V; beschermingsgraad IP20; PC3; driver niet inbegrepen; lamp niet inbegrepen;





WEVER & DUCRÉ  
LIGHTING

# DEEP 1.0 MR16

112110W0

## ELEKTRISCH

### Driver

TYPE	L · W · H (MM)	ORDERCODE
10W   12V	102-51-30	9 0 2 2 1 4 0 1
25W   12V	145-51-29.5	9 0 2 2 1 7 0 1
70W   12V	108-52-33	9 0 2 2 1 9 0 4