

## ToLEDo Retro Pygmy

ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL

0029540



### Product features

- Perfect for decorative and general lighting applications and creates a warm ambience similar to traditional lamps  
The versatile ToLEDo Retro ball range is the ideal replacement for halogen and incandescent lamps and perfect for chandeliers and decorative applications  
Same look, size and functionality as incandescent lamps  
Omni-directional light distribution  
Gives same sparkling light effect as the incandescent lamp  
Dimensionally identical to incandescent lamps - fits all fixtures  
Environment-friendly - no mercury and lower CO2 emissions  
Dimmable with approved dimmers



### NOTES

undefined

### PRODUCT OVERVIEW

Product name	ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
ETIM Class	EC001959
E-number FI	4740957
Warranty	3 years
Luminous flux (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Wattage (W)	2.5
Product Voltage (V)	230
Dimmable	No

## ToLEDo Retro Pygmy

ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL

0029540

Average life (Nominal) (h)	15000
Product EAN number	5410288295404

### DATA TABLE

#### General data

Product name	ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL
Technology	LED
Watt (Rated) (W)	2.5
Type	LED exchangeable
Cap/Base	E14
Fixture rating	Open
General application	Hospitality, Residential & Consumer
Operating temperature range (°C)	-20°C...+40°C
Performance ambient temperature Tq (°C)	25
ETIM Class	EC001959
E-number FI	4740957
Warranty	3 years

#### Optical data

Luminous flux (lm)	250
Luminous flux (Rated) (lm)	250
Colour temperature (K)	2700
Light colour	Homelight
CRI (Ra)	80
Colour Variation Initial (SDCM)	SDCM6
Photobiological Risk Group	RG1
Lumen maintenance at end of nominal life (%)	70

#### Electrical data

Wattage (W)	2.5
Equivalent watt (W)	25
Product Voltage (V)	230
Control gear required	No
No. Of switching cycles before premature failures	>50000
Transformer required	No
Dimmable	No
Inrush Current (A)	5.9
Inrush Duration (µs)	180
Lamp Energy Label (class)	F
Nominal Frequency (Hz)	50/60Hz
Max. Luminaires per 16A C Breaker	27
Max. Luminaires per 16A B Breaker	14

#### Lifetime data

Lifespan L70 B50	15000
------------------	-------

## ToLEDo Retro Pygmy

ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL

0029540

Average life (Nominal) (h)	15000
Average life (Rated) (h)	15000

### Physical data

Nominal Product Length (mm)	61
Nominal Product Diameter (mm)	26
Weight (kg)	0.015


### Packaging

Single packaging type	Carton
Product EAN number	5410288295404
Packaging single length / height (cm)	9.5
Packaging single width (cm)	5.0
Packaging single depth (cm)	5.0
DUN14 (outer)	15410288295401
Units per outer package	6
Packaging outer length / height (cm)	15.8
Packaging outer width (cm)	10.7
Packaging outer depth (cm)	10.5

### Safety data

Optimal operating condition (°C)	-20-40
Breakage cleaning instructions	Not applicable
Special purpose lamp	No
Dry applications use only	Yes
Suitable for household illumination	Yes
Safety message	Not Suitable for totally enclosed fixtures


## PHOTOMETRY




## TECHNICAL DRAWINGS

## ToLEDo Retro Pygmy

ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL  
0029540



0029540



**3**  
kWh/1000h



2019/2015

# SYLVANIA


## ToLEDo Retro Pygmy

ToLEDo RT PYGMY V5 CL 250LM 827 E14 SL

0029540



0029540



**3**  
kWh/1000h



2019/2015