

K72 IP54 LED GE


K already earned its spurs in the Modular range. With the LED dedicated rework of the K we honour an icon. A timeless product that will remain in the Modular portfolio for many years to come. Suitable for general and accent lighting, K is available in donkey grey and white structure.

Art. Nr. 14040609

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 65 h 60	
Weight	0.19kg	
Min. Distance	0.1	
IP	IP54	
Glow Wire Test	960°	
CRI	90	
Power supply	500	350
	18.4	17.8
Connected load	9.2W	6.2W
Lumen	792lm	590lm
Efficacy	86lm/W	95lm/W
UGR	22	21
Adjustability	Not Applicable	
Remark	! 3500K on request	

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+			NEUTRAL WHITE 4000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
donkey grey struc	14040071	14040171	14040271	14040371	14040471	14040571	14040671	14040771	14040871
white struc	14040009	14040109	14040209	14040309	14040409	14040509	14040609	14040709	14040809



This label is available in other languages:
<http://supermodular.com/assets/TYPE2.pdf>



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

K72 IP54 LED GE

ACCESSORIES

CONBOX

10490330 | CONBOX 112X172X100X236

DRIVER-LED

12403730 | LED GEAR 350MA 15W

