



Hermetic distribution board RH-36/2

Symbol:
RH-36/2

Catalogue number:
36.136

EAN:
5905548288413

Cat. No.	36.136
Symbol	RH-36/2
Typee	2 x 18
Version	-
Terminals N+PE	yes
Dimension A	435 mm
Dimension B	420 mm
Dimension C	138 mm



1 pc.

Specifications

Technical data

Colour	white
Material	ABS / PC
Operating temperature	-25°C to 60°C
Protection degree	IP 65
Protection class	Class II
Impact resistance	IK 07
Voltage	230/400 V AC
Maximum wire cross-section	10 mm
Reference standard	PN-EN 62208:2006; EN 62208: 2003
Version	B - white doors Z – metal lock

RH "NEO series" Hermetic distribution boards are used in households and industry with a possibility of installation of overload switches and electrical devices. They are available in the surface mounting version and are widely used outside in building wiring systems.

Technical data:

- the distribution boards are equipped with transparent dimmed door that open sideways (to the left or to the right), they are adjusted to mount a key lock,
- available in white,
- made of a high quality >ABS< plastic resistant to high temperatures up to 960 °C (hot rod test - it refers to a terminal block)),
- operating stability from -25 °C to + 60 °C,
- impact resistance (IK 07 degree),
- mounting possibility of devices of 68mm and 75 mm deep,
- 12 module models and bigger are equipped with weakening in walls for wire and pipe insertion (glands),
- door sealing possibility,
- the distribution boards are equipped with: terminal blocks for N an PE circuits, TH-35 DIN rail, self-adhesive tape for labels.

CONTACT

ELEKTRO-PLAST / DZ. SPRZEDAŻY / LOGISTYKA

address: 62-800 NIEDŹWIADY, Niedźwiady 24 k/Kalisza

phone: +48 (62) 76-70-376

e-mail: biuro@elektro-plast.pl



System
zarządzania
ISO 9001:2008
www.tuev.com
© 201002279

