


# LED PRO-CEILING SERIE (IP40)


Opbouw (Surface mounted)



## LED Pro-Ceiling ø 240mm 15W incl. LED voeding (driver)



CE IP40   



- LED Pro-Ceiling ø 240mm.
- Behuizing gemaakt uit gegoten aluminium, gepoederlakt in wit, grijs of zwart.
- Lichtterugval tot een minimum beperkt doordat de behuizing tevens fungeert als koellichaam.
- Uitgevoerd met melkwitte acrylaat lens.
- Verkrijgbaar in verschillende kleurtemperaturen.
- Wordt compleet geleverd met geïntegreerde voeding.

Toepassingsgebieden: verlichting van gangen, trappenhuizen, toiletten, etc.

- LED Pro-Ceiling ø 240mm.
- Housing made of die-cast aluminum, powdercoated in white, grey or black.
- Excellent heat sink capability to minimize the luminous degradation.
- Equipped with a milky acrylic lens.
- Available in various color temperatures.
- Integral LED driver included.

Applications: lighting of hallways, staircases, toilets, etc.

40001/ .. / 2 / ..

### Kleurtemperatuur Color temperature

- 0: Warm wit, 3000K  
Warm white
- 1: Puur wit, 4200K  
Pure White
- 2: Koud wit, 6500K  
Cool White
- 5: Warm wit, 3000K, dimbaar  
Warm white, dimmable
- 6: Puur wit, 4200K, dimbaar  
Pure White, dimmable
- 7: Koud wit, 6500K, dimbaar  
Cool White, dimmable

### Armatuurkleur Fixture color

- 1: Wit  
White
- 2: Zwart  
Black
- 3: Grijs  
Grey

Lichtbron (Light source): SMD LED's

Kleurtemperatuur (Color temperature): 3000K (Warm wit) (Warm white), 4200K (Puur wit) (Pure white), 6500K (Koud wit) (Cool white)

Lichtstroom (Light output): 1006LM/1118LM/1118LM

Bedrijfstemperatuur (Operating temperature): -10° C - +40° C

Aantal branduren (Rated life hours): 35,000 - 50,000

LED voeding (inclusief) (LED driver (included)): CE, TUV

Voedingsspanning (Input): 220-240V AC 50/60Hz

Cosinus phi (Power factor): > 0.90

Verlichtingshoek (Beam angle): 110°

Opgenomen vermogen (inclusief voeding) (Power consumption (driver included)): 15W

LED Pro-Ceiling ø 240mm  
15W

