





SLIDE IP54 LED GE

Slide is one of the Modular icons. Its name refers to the light gliding out from the luminaire, channelled by the stunning inner body, and creating a softer and smooth lighting experience. Slide owes its popularity to its deeply embedded light source. It is available in the Modular donkey grey structure with black inner body or in an entirely white structure version.

PECIFICATIONS		
Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Cut-out size	ø 92 h 75	
Weight	0.3kg	
Min. Distance	0.1	
IP	IP54	
Glow Wire Test	960°	
CRI	90	
Power supply	350mA	500mA
	16.5Vf	17.1Vf
Connected load	6.2W	9.2W
Lumen	324lm	416lm
Efficacy	52lm/W	451m/W
UGR	6	7
Adjustability	Not Applicable	
Remark	! 3500K and 4000K or	n request
MODULAR This luminaire contains built-in LED lamps. AP AP AP B C D E The lamps cannot be changed in the luminaire.	This labe	el is available in other languages: permodular.com/assets/TYPE2.pdf

	WARM WHITE 2700K / CRI 90+	WARM WHITE 3000K / CRI 90+
	MEDIUM 25°	MEDIUM 25°
donkey grey struc	10486174	10486374
white struc	10486109	10486309

Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.

SLIDE



SLIDE IP54	LED GE
ACCESSORIES	
GYPKIT	
12290330	GYPKIT 190X190 - Ø92
CONBOX	
10889830	CONBOX 190X192X130X256