



PLASTIC BLIND STOPS SERIES

Plastic series are separated from other blind stops due to the following characteristics;

- Polyamide raw material
- High heat and impact resistance
- Resistance to Ultraviolet rays
- IP54 protection class
- Connection thread norms (DIN 40430 / EN 60423)
- Continuous heat resistance -30 °C +80 °C
- Short term temperature range +150 °C
- Halogen free (not contain poisonous gas)

POLYAMIDE  
BLIND STOPS



Polyamid  
RAL 7001  
RAL 7035  
RAL 9005  
EN 60423  
DIN 40430  
IP 54  
- 30 °C + 80 °C  
+150 °C



■ RAL 7001    ■ RAL 7035    ■ RAL 9005

METRIC/PG THREAD BLIND STOPS

AG Thread	Gray Code	L. Gray Code	Black Code	H mm	GL mm	D mm	IP 54 Halogen free
	■ RAL 7001	■ RAL 7035	■ RAL 9005				
M 12 x 1,5		01		8,5	6	15	
M 16 x 1,5		02		10	7	20	
M 20 x 1,5		03		10	7	24	
M 25 x 1,5		04		14	10	30	
M 32 x 1,5		05		14	10	37	
M 40 x 1,5		06		15	10	48	

PRODUCT RANGE OVERVIEW