





ENTERO RD-S TRIMLESS IP TW 94045 GC

28472 9030 GC

BESCHIKBAAR IN
ZWART 28472 9030 B
GOUD KLEUR 28472 9030 GC
WIT 28472 9030 W



[Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - Ø KIT
INBOUWDIEPTE (MM)	115
STOF EN WATERDICHTHEID	IP44/20
GEWICHT (KG)	0.245
RICHTBAARHEID	0° tot 20° zwenkbaar, 355° roteerbaar
INFO	REFLECTOR WFL-45° EXCL.LED POWER SUPPLY 500mA-DC TW - (DALI DT8)

Elektrische info

KLASSE	III
ENERGIE KLASSE	E

Info lichtbron

Lightsource Name	LED
Lichtbron	LED array 9W / CRI>90 (R9: 50) / 1800K-4000K / 979lm
TM-30-15 Waarden	Rf: 89 / Rg: 100
SDCM	SDCM2
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	979lm // 9W // 109lm/W
LED techniek (toestel)	636lm // 10W // 61lm/W

Benodigdheden























MOUNTING KIT ENTERO ROUND S
MOUNTING KIT AIR 105
LED POWER SUPPLY 500mA-DC TW

ENTERO RD-S TRIMLESS IP TW 94045 GC

28472 9030 GC

Voor gedetailleerde montage gegevens, consulteer de handleiding: [28472_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	-	
 Plasterboard	-	
 Stucanet	-	
 Wood	-	
 Concrete	 ENTERO RD-S MOUNTING SET S2	Required
 Concrete + plaster	 ENTERO RD-S MOUNTING SET S2	Required
 Lintel + plaster	 ENTERO RD-S MOUNTING SET S2	Required
 Hollow-core slab	 ENTERO RD-S MOUNTING SET S2	Required
 Hollow-core slab + plaster	 ENTERO RD-S MOUNTING SET S2	Required
 Stretched ceiling	-	
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR ONLY 1	Required
	 MOUNTING KIT SIDE AIR 105	Required
	 MOUNTING KIT NO AIR 105	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 105	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required


ENTERO RD-S TRIMLESS IP TW 94045 GC

28472 9030 GC

VERVOLLEDIG UW SPECIFICATIE

LED voedingen

#



21012 0355 LED POWER SUPPLY 500mA-DC 2CH TW DIM5


1->2

Montage kit



28400 0010 MOUNTING KIT ENTERO RD-S O.F.A.

Montage kit spanplafond




28400 0070 MOUNTING KIT ENTERO RD-S CSC



28400 0130 MOUNTING KIT ENTERO RD-S WSC

Montage kit - side air + light




29810 0110 MOUNTING KIT SIDE AIR 105

ENTERO RD-S TRIMLESS IP TW 94045 GC


28472 9030 GC

Montage kit - side air only




29810 0100 MOUNTING KIT SIDE AIR ONLY 1

Montage kit - top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1

Montage kit - no air



29810 0120 MOUNTING KIT NO AIR 105

Notes: