



M-LED 50 GE

With the introduction of the in-house developed M-LED modules, we are preparing some of our icons for the future. The M-LED 111 module is replacing the AR111 lamp and comes in white structure or black matt. M-LED 111 is applicable for following 'AR111' (GE) luminaires: Bolster recessed, Nomad, Multiple, Multiple trimless, Lotis, Haloscan and Thub metal. Also fits AR111 modules of SL149, Multiple(x), Freeway, 2FLAT2C and Traffic. M-LED 70 is replacing the well-known AR70 lamp. The M-LED 70 module is applicable for 'AR70' luminaires such as Mini multiple and Haloscan 128.

Art. Nr. 14060505

SPECIFICATIONS

Lamp	1x LED Array	
Gear / Transfo	LED gear not incl.	
Weight	0.14kg	
Min. Distance		
IP	IP20	
Glow Wire Test		
Power supply	350mA	500mA
	17.8Vf	18.4Vf
Connected load	6.2W	9.2W
Lumen	605lm	813lm
Efficacy	98lm/W	88lm/W
UGR	21	22
Adjustability	Not Applicable	

	WARM WHITE 2700K / CRI +			WARM WHITE 3000K / CRI +			NEUTRAL WHITE 3500K / CRI +			NEUTRAL WHITE 4000K / CRI +		
	SPOT	MEDIUM	FLOOD	SPOT	MEDIUM	FLOOD	SPOT	MEDIUM	FLOOD	SPOT	MEDIUM	FLOOD
alu	14060005	14060105	14060205	14060305	14060405	14060505	14060605	14060705	14060805	14060905	14061005	14061105



Modular reserves the right to alter material, dimensions and characteristics without prior notice. Lighting technology changes rapidly. Latest datasheet and documentation available on www.supermodular.com.