

WINK 115 LED GE


Wink may be recessed, and therefore discreet, but its technical ingenuity is nothing short of remarkable, so is its sense of humour. As its name suggests, it likes to wink at you. The streamlined design, where elegance meets high-quality finish, results in a fixture that is half hidden in the ceiling and half peeking out. It has all the features to become a new Modular icon.

Art. Nr. 13070032

SPECIFICATIONS

Lamp	1x LED Array			
Gear / Transfo	LED gear not incl.			
Cut-out size	ø 146 h 100			
Weight	0.86kg			
Min. Distance	0.1m			
IP	IP54			
Glow Wire Test	960°			
CRI	90			
Power supply	700mA	900mA	350mA	500mA
	31Vf	31.7Vf	29.1Vf	29.9Vf
Connected load	23.4W	31W	11W	16.2W
Lumen	1758lm	2072lm	963lm	1322lm
Efficacy	76lm/W	67lm/W	88lm/W	83lm/W
UGR	22	23	20	21
Adjustability	h 355°			
Remark	! 3500K and 4000K on request			

	WARM WHITE 2700K / CRI 90+			WARM WHITE 3000K / CRI 90+		
	SPOT 15°	MEDIUM 25°	FLOOD 40°	SPOT 15°	MEDIUM 25°	FLOOD 40°
black struc	13070032	13070332	13070632	13070132	13070432	13070732
white struc	13070009	13070309	13070609	13070109	13070409	13070709



This label is available in other languages:
<http://supermodular.com/assets/TYPE2.pdf>

