



VARO FLAT 93036 S1 B

21917 9320 B

BESCHIKBAAR IN
ZWART 21917 9320 B
WIT 21917 9320 W



 [Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - 76
INBOUWDIEPTE (MM)	50
DIKTE MONTAGEOPPERVLAK (MM)	min.5
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.3
RICHTBAARHEID	niet richtbaar
INFO	LENS FL-36° EXCL.LED POWER SUPPLY 350mA-DC

Elektrische info

KLASSE	III
ENERGIE KLASSE	E

Info lichtbron

Lightsource Name	LED
Lichtbron	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30-15 Waarden	Rf: 90 / Rg: 99
SDCM	SDCM2
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	812lm // 7,1W // 115lm/W
LED techniek (toestel)	536lm // 8W // 66lm/W

Benodigdheden

LED POWER SUPPLY 350mA-DC DIM

Opties

PLASTERKIT 101

VARO FLAT 93036 S1 B

21917 9320 B

Voor gedetailleerde montage gegevens, consulteer de handleiding: [21917_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit	
 System ceiling	-	
 Plasterboard	-	
 Stucanet	 PLASTERKIT 101	Required
 Wood	-	
 Concrete + plaster	 PLASTERKIT 101	Required
 Lintel + plaster	 PLASTERKIT 101	Required
 Hollow-core slab + plaster	 PLASTERKIT 101	Required
 Stretched ceiling	-	


VARO FLAT 93036 S1 B

21917 9320 B

VERVOLLEDIG UW SPECIFICATIE

LED voedingen


#



300 90 91

LED POWER SUPPLY 350mA-DC / 15W


2(1)



300 90 108 U

LED POWER SUPPLY 350mA-DC / 8W


1



300 90 124

LED POWER SUPPLY MULTI-POWER DIM7


2 (2)



300 90 125

LED POWER SUPPLY MULTI-POWER MINI DIM5


2 (2)



21012 0258

LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1



21012 0268

LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2

Pleisterkits



202 11 19 PLASTERKIT 101

VARO FLAT 93036 S1 B

21917 9320 B

Notes: