



LOTIS 97 CONCRETE ADJUSTABLE FOR LED GE

Lotis is the recessed spotlight which started it all. The hallmark of this luminaire, is the deeply recessed cone which holds the light source and has a fine edge. Lotis comes in different diameters and with different lighting sources. Lotis 48 is particularly fitted to use in wall mounted application.

Art. Nr. 13100109

SPECIFICATIONS

Lamp	1x LED (not incl.)
Gear / Transfo	LED gear not incl.
Cut-out size	ø 92 h 100
Weight	0.17kg
Min. Distance	0.1 m
Power supply	
IP	IP20
Glow Wire Test	960°
Adjustability	v -15°/+15°
Remark	! must be used with M-LED 50

black	13100102
white struc	13100109



LOTIS 97 CONCRETE ADJUSTABLE FOR LED GE

ACCESSORIES

M-LED

14060005	M-LED 50 2700K SPOT GE ALU
14060105	M-LED 50 2700K MEDIUM GE ALU
14060205	M-LED 50 2700K FLOOD GE ALU
14060305	M-LED 50 3000K SPOT GE ALU
14060405	M-LED 50 3000K MEDIUM GE ALU
14060505	M-LED 50 3000K FLOOD GE ALU
14060605	M-LED 50 3500K SPOT GE ALU
14060705	M-LED 50 3500K MEDIUM GE ALU
14060805	M-LED 50 3500K FLOOD GE ALU
14060905	M-LED 50 4000K SPOT GE ALU
14061005	M-LED 50 4000K MEDIUM GE ALU
14061105	M-LED 50 4000K FLOOD GE ALU



