





VARO S OK 93045 B

21932 9320 B

BESCHIKBAAR IN
ZWART 21932 9320 B
WIT 21932 9320 W



 [Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	square - 85 x 85
INBOUWDIEPTE (MM)	75
DIKTE MONTAGEOPPERVLAK (MM)	max.25
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.2
RICHTBAARHEID	0° tot 25° zwenkbaar, 350° roteerbaar
INFO	REFLECTOR FL-45° EXCL.LED POWER SUPPLY 350mA-DC VARO S OK COVER BLACK or WHITE included

Elektrische info

KLASSE	III
ENERGIE KLASSE	D

Info lichtbron

Lightsource Name	LED
Lichtbron	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30-15 Waarden	Rf: 90 / Rg: 99
SDCM	SDCM1
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	787lm // 5,8W // 135lm/W
LED techniek (toestel)	541lm // 7W // 81lm/W

Benodigheden

LED POWER SUPPLY 350mA-DC DIM

Opties

VARO S OK COVER

Voor gedetailleerde montage gegevens, consulteer de handleiding: [21932_XXX0_HAND.pdf](#)


PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

VERVOLLEDIG UW SPECIFICATIE


LED voedingen

#




300 90 91 LED POWER SUPPLY 350mA-DC / 15W

2(1)




300 90 108 U LED POWER SUPPLY 350mA-DC / 8W

1(1)




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

3(2)




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

2(2)



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8


1



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

Decoratieve ornamenten



21910 0030 B VARO S COVER B

21910 0030 MMAT VARO S COVER MMAT

 DELTALIGHT®

VARO S OK 93045 B

21932 9320 B

Notes: