





DEEPER

CEILING RECESSED



1.0 LED

LED 7/10W | 350-500mA | 18Vf
COB 3-step | excl. power supply
aluminium powder coated

0.17kg IP20 3-0.3-D P 36°

76 95 4-30

	CODE
	152161W
	152161S
	152161B

Light Colour Selection

	LUMEN CRI	CODE
2700K	420-590 >90	3
3000K	470-640 >90	5
1800-2850K	320-440 >95	9

ALWAYS USE

power supply

	CODE
350mA 10W	90223401
500mA 10W	90214404
500mA 15W dim	90224501

more power supplies on page 574

1.0 MR16

QR-CBC51 max.35W | GU5.3
12V | excl. power supply
aluminium powder coated

0.11kg IP20 0.9-D

76 100 4-30

	CODE
	152110W0
	152110S0
	152110B0

ALWAYS USE

power supply

	CODE
12V 10W dim	90221401
12V 25W dim	90221701
12V 70W dim	90221904

more specs on page 576

1.0 PAR16

PAR16 max.35W | GU10
100-240VAC | 50-60Hz
aluminium powder coated

0.15kg IP20 0.9-D

76 115 4-30

	CODE
	152120W0
	152120S0
	152120B0

OPTIONAL

PAR16 LED GU10 7W
phase-cut dim

	CODE
2700K	901228W2
3000K	901228W4
1800-2850K	901229S9

more lamps and specs on page 577