


Y-CONNECTOR | Branching for light management systems



Areas of application

- Suitable for all OSRAM components with modular 4p4c connector system

Product benefits

- For parallel connection of sensors to a MULTieco, MULTI 3, DALieco system
- Enables synchronization and connection of multiple EASY system components


Product features

- Passive distributor
- Connections: 3x modular 4p4c socket
- Type of installation: Adhesive pad mounting on smooth surfaces

Product datasheet

Technical data

Dimensions & weight



Length	34.0 mm
Width	18.0 mm
Height	16.0 mm
Product weight	80.00 g





Certificates & standards

Type of protection	IP20
--------------------	------

Equipment / Accessories

- 2 connecting cables included, modular 4p4c connector on both ends, length 2.1 m

Download Data

File	
	Brochures Non-system-specific components brochure
	Brochures Application Guide EASY lighting control (EN)
	Declarations of conformity LMS MULTI3 SENSORS
	Installation/Operation notice Y-CONNECTOR branch element

Logistical Data

Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300803135		Shipping carton box 25	224 mm x 190 mm x 220 mm	9.36 dm ³	2465.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.