





## VARO 2 S OK 92745 B

21933 9220 B

BESCHIKBAAR IN  
**ZWART** 21933 9220 B  
**WIT** 21933 9220 W



 [Bekijk op website](#)

### Algemene info

<b>LOCATIE</b>	binnen
<b>INSTALLATIE</b>	Plafond Inbouw
<b>ZAAGMAAT/OPENING (MM)</b>	square - 165 x 85
<b>INBOUWDIEPTE (MM)</b>	75
<b>DIKTE MONTAGEOPPERVLAK (MM)</b>	max.25
<b>STOF EN WATERDICHTHEID</b>	IP20
<b>GEWICHT (KG)</b>	0.3
<b>RICHTBAARHEID</b>	0° tot 20° zwenkbaar, 350° roteerbaar
<b>INFO</b>	REFLECTOR FL-45° EXCL.LED POWER SUPPLY 350mA-DC VARO 2 S OK COVER BLACK or WHITE included

### Elektrische info

<b>KLASSE</b>	III
<b>ENERGIE KLASSE</b>	D

### Info lichtbron

Lightsource Name	LED
Lichtbron	2 x (LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm)
TM-30-15 Waarden	Rf: 89 / Rg: 100
SDCM	SDCM1
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	1506lm // 11,6W // 129lm/W
LED techniek (toestel)	1035lm // 13W // 78lm/W

### Benodigdheden

LED POWER SUPPLY 350mA-DC DIM

### Opties

VARO 2 S OK COVER

Voor gedetailleerde montage gegevens, consulteer de handleiding: [21933\\_XXX0\\_HAND.pdf](#)

## PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-


**VARO 2 S OK 92745 B**

21933 9220 B

**VERVOLLEDIG UW SPECIFICATIE**


**LED voedingen**

#



**300 90 91** LED POWER SUPPLY 350mA-DC / 15W

2(1/2)




**300 90 108 U** LED POWER SUPPLY 350mA-DC / 8W

1/2 (1/2)




**300 90 124** LED POWER SUPPLY MULTI-POWER DIM7

1(1)




**300 90 125** LED POWER SUPPLY MULTI-POWER MINI DIM5

1(1)



**21012 0258** LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8


1/2



**21012 0268** LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

1

**Decoratieve ornamenten**



**21910 0040 B** VARO 2 S COVER B

**21910 0040 MMAT** VARO 2 S COVER MMAT

 DELTALIGHT®

**VARO 2 S OK 92745 B**

21933 9220 B

Notes: