





VARO FLAT 93036 S1 W

21917 9320 W

BESCHIKBAAR IN
ZWART 21917 9320 B
WIT 21917 9320 W



 [Bekijk op website](#)

Algemene info

LOCATIE	binnen
INSTALLATIE	Plafond Inbouw
ZAAGMAAT/OPENING (MM)	rond - 76
INBOUWDIEPTE (MM)	50
DIKTE MONTAGEOPPERVLAK (MM)	min.5
STOF EN WATERDICHTHEID	IP20
GEWICHT (KG)	0.3
RICHTBAARHEID	niet richtbaar
INFO	LENS FL-36° EXCL.LED POWER SUPPLY 350mA-DC

Elektrische info

KLASSE	III
ENERGIE KLASSE	E

Info lichtbron

Lightsource Name	LED
Lichtbron	LED array 7,1W / CRI>90 (R9: 52) / 3000K / 812lm
TM-30-15 Waarden	Rf: 90 / Rg: 99
SDCM	SDCM2
Risk-groep	RG1
LM80	L90B10 > 50000
LED techniek (lichtbron)	812lm // 7,1W // 115lm/W
LED techniek (toestel)	536lm // 8W // 66lm/W

Benodigdheden

LED POWER SUPPLY 350mA-DC DIM

Opties













PLASTERKIT 101

VARO FLAT 93036 S1 W

21917 9320 W

Voor gedetailleerde montage gegevens, consulteer de handleiding: [21917_XXX0_HAND.pdf](#)

PLAFOND COMPATIBILITEIT

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	 PLASTERKIT 101 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 101 Required
 Lintel + plaster	 PLASTERKIT 101 Required
 Hollow-core slab + plaster	 PLASTERKIT 101 Required
 Stretched ceiling	-


VARO FLAT 93036 S1 W

21917 9320 W

VERVOLLEDIG UW SPECIFICATIE


LED voedingen

#



300 90 91 LED POWER SUPPLY 350mA-DC / 15W

2(1)



300 90 108 U LED POWER SUPPLY 350mA-DC / 8W

1




300 90 124 LED POWER SUPPLY MULTI-POWER DIM7

2 (2)




300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5

2 (2)



21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2

Pleisterkits



202 11 19 PLASTERKIT 101



VARO FLAT 93036 S1 W

21917 9320 W

Notes: